

Fig. 7: Frequency response of band-reject filter with $N=67$, $f_l=1.2$ and $f_u=2.0$

EFY Note

The source code of this project is included in this month's EFY DVD and is also available for free download on source.efymag.com

frequency (f_u)=2.0, is shown in Fig. 7. Frequency response of band-pass filter with $N=91$, $f_l=1.2$ and $f_u=2.0$ is shown in Fig. 8.

The program was tested on Win-




Fig. 8: Frequency response of band-pass filter with $N=91$, $f_l=1.2$ and $f_u=2.0$

dows XP, 32-bit PC using Turbo C++ version 3. For running Turbo C++ on 64-bit PC with Windows 7 or Windows 8, a separate Turbo C++ IDE is available for download. You need to copy the source code and relevant header files into bin folder before running the program.

Applications

Digital signal processing finds application in almost every field of engineer-

ing. These filters can also be used in applications like noise removal. The filter routines can be easily coded to hardware description language like Verilog or VHDL and can turn out to be a good project for students or designers working in real-time image and video processing. ●

The author is an M.Tech from ABV-Indian Institute of Information Technology and Management, Gwalior, and B.Tech from Jamia Millia Islamia in New Delhi

INDUSTRIAL POWER EXPERT

MORNSUN® is not only a manufacturer but also provides added value & solutions with our innovative unique designs and products.

Certification: ISO9001:2008, ISO14000, OHMSMS18001, and TS16949; UL60950, EN60950, UL60601-1, EN60601-1



DC-DC converters extensive range 1/4W to 100W

AC-DC converters wide range 1W to 120W

Packages Available: PCB MOUNT, CHASSIS MOUNT, SMD, DIP, SIP, and DIN RAIL

MORNSUN®

Email: info@mornsun.cn
<http://www.mornsun-power.com>

MORE THAN RELIABILITY

