

Brand	Component	Takeaway according to manufacturer
Freescall	Kinetis E series MCUs	Electromagnetic noise immunity for systems that traditionally use 8- and 16-bit MCUs while providing high efficiency and optimal code density.
Freescall	Kinetis miniature (mini) MCUs	World's smallest ARM powered MCU; ideal for small and smart applications.
Freescall	Kinetis KW2x wireless MCUs	Best-in-class 802.15.4/ZigBee wireless solutions. Integrates ARM Cortex-M4 processor, and a 802.15.4 standard-compliant RF transceiver, and provides a reliable, secure, low-power 2.4GHz platform.
Freescall	QorIQ T2080 processor	Dual-threaded, 64-bit Power Architecture-based device engineered for optimal network performance and energy efficiency.
Freescall	Freescall Kinetis M series MCU	Designed for single-chip 1, 2 and 3-phase electricity meters and other precision measurement applications. Multiple 24-bit Sigma Delta ADCs, programmable gain amplifiers, voltage reference with low drift over temperature, phase-shift compensator. Security features including a memory protection unit, external tamper detection pins, IRTC with tamper detect and a random number generator provide protection of supplier/user data within the MCU and from the MCU to the power grid.
Freescall	Kinetis L series MCUs	32-bit devices help enable ultra-low-power designs for handheld appliances, portable medical products and consumer electronics applications.
Microchip	Digitally enhanced power analogue controller	Range of intelligent DC/DC power-conversion solutions grows to include controllers supporting flyback, boost and SEPIC topologies. Introduced a step-up PWM controller and low-side MOSFET driver architecture, with a mid-voltage LDO and fully-functional MCU - all integrated into a small, high-density power package.
Microchip	Motor driver	Cost-effective, world's first 1.5A, three-phase brushless DC, sinusoidal motor driver in a 4x4mm package with the AEC-Q100 quality certification.
Microchip	8-bit PIC MCU	Rich set of intelligent analogue and core-independent peripherals (offload timing-critical and core-intensive tasks from the CPU), along with cost-effective pricing and extreme low power (XLP) technology.
Microchip	Projected-capacitive touch controllers	Industry's lowest-power, integrates capacitive scanning for touch-screens and touch-pads including 11 single-finger gestures to swipe, scroll or double tap.
Microchip	Energy-measurement analogue front ends (AFE)	Integrate six and eight 24-bit, delta-sigma ADCs, respectively, with 94.5dB SINAD, -106.5dB THD and 112dB SFDR for high-accuracy signal acquisition and higher-performing end products. Two extra ADCs enable the monitoring of more sensors with one chip, lowering cost and size.
Microchip	Sensor hub	Low-power, flexible sensor hub that makes implementing sensor fusion easy and provides an extremely large selection of supported sensors, for Windows 8-based PCs, 2-in-1 convertibles, tablets and gaming applications.
Microchip	50-ohm matched WLAN front end Module	Small package and footprint, for high data rate mobile device applications.
Microchip	PIC32MZ 32-bit MCUs	Integrate 2MB Flash, 512kb RAM, 28Mbps ADC, crypto engine, hi-speed USB, 10/100 Ethernet, CAN and many serial channels. High performance, high memory and peripheral integration.
Microchip	Power monitoring IC	Highly integrated, single-phase power-monitoring IC designed for real-time measurement of AC power.
Microchip	PIC24FJ128GC010 MCU family	Analogue SoC that integrates a full analogue signal chain, including Microchip's first ever on-chip precision 16-bit ADC and 10Mbps 12-bit ADC, plus a DAC and dual op-amps, along with extreme low power (XLP) technology for extended battery life in portable medical and industrial applications.
Lattice	ECP5 FPGA	Combines 40% lower-cost, 30% lower power and 2x functional density in the smallest package to meet the unique needs of fast-growing high-volume small-cell, micro server, broadband access and video applications.
Lattice	MachXO3 FPGAs	World's smallest, lowest-cost-per I/O programmable platform aimed at expanding system capabilities and bridging emerging connectivity interfaces using both parallel and serial I/O.
Lattice	ICE40 FPGA family	Flexible, single-chip sensor solutions for making a new generation of context-aware, ultra-low-power mobile devices possible. Enables always-on sensor solutions.
Lattice	Automotive grade ECP3 FPGAs	Smallest automotive-qualified FPGA with SERDES. Improve fuel efficiency, safety and access to entertainment.
Atmel	ATPL230A PLC modem	Seamless and cost-efficient solution for smart metering platforms, providing best-in-class modem features.
Atmel	SmartConnect Wi-Fi connectivity	Integrates Atmel's ultra-low-power MCUs and wireless connectivity solutions into an easy, turnkey IoT solution.
Atmel	SAM D Cortex M0+ based MCU portfolio	Entry-level, low-power MCUs packed with high-end features including Atmel's patented Event System, SERCOM module, peripheral touch controller, along with a full-speed USB interface. Additional connectivity and communication options.
Atmel	LIN System Basis Chip (SBC)	Lower power consumption, improved LDO works down to 2.3V, MLC blocking capacitors for lower overall system cost - industry's first device that complies with the new OEM hardware recommendations.
Atmel	Cortex-A5 processor-based MPUs	Smaller packaging, extended temperature support, and an alternative peripheral mix while maintaining high performance and low-power operation along with an expanded ecosystem to include new software and hardware solutions.
Atmel	Smart RF receiver IC family	Lower power consumption, high sensitivity and excellent out-of-band blocking performance.