

THE LEADING RELAY R&D AND MANUFACTURING BASE GLOBALLY

Xiamen Hongfa Electroacoustic Co. Ltd is the first largest relay manufacturer in China and one of the leading relay manufacturers and suppliers in the world. It produces a wide range of products, including relays, low-voltage devices, precision components and automatic equipments. In particular, it has over 160 types of relay categories, including power relays, latching relays, automotive relays, signal relays, industrial & electrical appliance relays, safety & electrical appliance relays, solar relays and hermetically sealed relays, which provide over 40,000 regular-used relay specifications.

POWER RELAY

UPS, Inverter, Control panel, Voltage stabilizer

HF3FA (215)



- 1 pole: 15A 125VAC, 10A 250VAC/28VDC
- Product in accordance to IEC 80335-1 available

HF3FF (215)



- 1 pole: 10A 277VAC/28VDC

HF14FW(136)



- TV-8, 20A switching capacity (1 pole configuration)
- 4kV dielectric strength
- Meeting VDE 0700, 0631 moisture insulation

UPS, Inverter

HF105F-1(136)



- 40A switching capacity
- 4kV dielectric strength (coil to contacts)
- Unenclosed, Plastic sealed and dust protected types available

Railways and Air-con.

HF102F



- Heavy load up to 5000VA
- Ideal for motor load (80A High inrush current)
- PCB & QC layouts available

Timers/Relay module

HF33F



- 1 pole: 10A 125VAC, 5A 250VAC/30VDC
- Creepage distance: 8mm (V0 to NC)
- High sensitivity 200mW available

Lighting application

HF46F



- 1 pole: 5A 277VAC/30VDC at 85°C
- Surge withstand voltage up to 10kV
- High sensitivity: 200mW

UPS

HF115FD



- 16A switching capacity
- Creepage distance: 10mm
- Updated version of HF115F
- 1 pole equipped with automatic production line

PLC Controller

HF49FD



- 3kV dielectric strength between coil and contacts
- Slim size: width 5mm, height 12.5mm
- High sensitive: min. 120mW

Air-con.

HF118F(136)



- 1 pole: 10A, 230V (2 pole): 5A
- dielectric strength: 5kV
- Creepage distance >8mm
- Reflow soldering available

Telecom, EPABX, Mobile tower

HFD27



- High contact capacity 2A 30VDC
- Matching 16 pin IC socket
- Epoxy sealed for automatic-wave soldering and cleaning

HFD23



- 1 Form C configuration
- 2A switching capacity
- High sensitive: 150mW
- Plastic sealed type available

HFD3



- Surge withstand voltage up to 2500VAC, meets FCC Part 68 and Telecordia
- SMT and DIP types available
- Single side stable and latching type available

Control panel



HF18FF / HF18FH

- 7A switching capacity (2C, 3C type)
- Various terminals, test button available
- Gold plated contact available
- 2 to 4 pole configurations



HF13F

- 15A switching capacity (1 Form C)
- Conform to the CE low voltage directive
- 1 & 2 pole configurations
- Various terminals available

AUTHORISED DISTRIBUTOR: _____



MILLENNIUM SEMICONDUCTORS

www.millenniumsemi.com

Corporate Office: 17/18/19, 2nd Floor, Mahalaxmi Heights, Mumbai-Pune Road, Pimpri, Pune 411 018, Maharashtra, INDIA.
Tel: 91-20-27484800, 27484900/27485000, 9921107771. Fax: 91-20-27421486, Email: kshiti@millenniumsemi.com



EN ISO 9001
Certificate Reg. No. 25130 92034167
www.tuv.srl

Branch Offices: • Ahmedabad • Bangalore • Chennai • Coimbatore • Delhi • Hyderabad • Mumbai