

COMPONENTS

Connectors

BarGuide connectors are developed to meet the ever-evolving demands for high-power distribution in high-density packaging and these are used



to provide high-amperage connections between busbars and circuit boards. These connectors provide a

current carrying capability of 60A to 250A, based on specific pins' sizes. These are available with press-fit PCB tails for mounting on both circuit boards and busbars and come in vertical and right-angle designs that can provide parallel or perpendicular interconnections.

BarGuide connectors provide a high-current, low-power-loss interconnection with a quick connect/disconnect function for space-constrained board-to-board, board-to-busbar and busbar-to-busbar power-distribution applications. These use high-performance springs, which provide a large surface contact area, thus ensuring small voltage loss, minimum heat generation, and low insertion and extraction forces.

FCI Electronics

Website: www.fci.com

Colour sensor

ROHM has developed a colour sensor for display-equipped devices, such as smartphones and tablets, capable



W50D08X2120
(2.0x2.1xMax0.6mm)

of detecting colour temperature, brightness and RGB components of ambient light.

The BH1745NUC leverages original infra-red (IR) removal technology and computing methods to achieve the industry's highest IR cut-off characteristics, reducing effects of IR rays by over 10x compared with conventional products. This enables compatibility with dark (low permeability) optical windows, unlike conventional colour sensors that cannot provide accurate detection due to the effects of IR interference when dark windows are used.

ROHM Semiconductor

Website: <http://www.rohm.com>

MOSFETs

TI's new CSD17573Q5B and CSD17577Q5A can be paired with LM27403 for DC/DC controller applications to form a complete synchro-



nous buck converter solution. These power MOSFETs improve energy efficiency in high-power computing, networking, industrial and power supplies.

Texas Instruments

Website: www.ti.com

Microcontrollers

Six new devices now join the entry-level 32-bit STM32F0 value line to address the 8-bit and 16-bit applications. These latest additions augment the strong feature-set of the STM32F0 value line, giving designers access to built-in safety functionalities, precise internal oscillators, multiple clock sources and a calendar real-time clock (RTC)

with alarm and periodic wake-up from stop/standby. Further important features include a five-channel DMA controller, internal voltage regulator, 12-bit/1.0µs analogue-to-digital converter (ADC) and versatile communication capabilities, such as two I2C interfaces, six USARTs and two SPIs.

STMicroelectronics

Phone: +91-120-2352999

Website: www.st.com

Reed switch

Littelfuse has released MACD-14 and MASM-14 series, a high-precision extension of its reed switch product line. (The MASM-14 is the surface mount version of the MACD-14.) MACD-14 and MASM-14 series offer these key features and benefits:

1. Through-hole, surface-mount and custom forms provide layout and design flexibility
2. Hermetically-sealed switch contacts are not affected by harsh environments
3. Close differential (low close/open hysteresis) provides precise switching for applications with limited space
4. Switching capability of 200V DC at up to 10W provides high-load-switching capability and flexibility in a compact package
5. Available sensitivity range of 10-30AT for high-accuracy performance under all operating conditions.

Littelfuse Inc.

Website: www.littelfuse.com

Insulated-gate bipolar transistor

This insulated-gate bipolar transistor (IGBT) from Infineon is optimised for low switching frequencies ranging from 50Hz to 20kHz. These can typically be found in applications such as uninterruptible power supplies (UPSs) as well as in inverters