

# THE LEADING RELAY R&D AND MANUFACTURING BASE GLOBALLY

Xiamen Hongfa Electroacoustic Co. Ltd is the first largest relay manufacturer in China and one of the leading relay manufacturers and suppliers in the world. It produces a wide range of products, including relays, low-voltage devices, precision components and automatic equipments. In particular, it has over 160 types of relay categories, including power relays, latching relays, automotive relays, signal relays, industrial & electrical appliance relays, safety & electrical appliance relays, solar relays and hermetically sealed relays, which provide over 40,000 regular-used relay specifications.

**POWER RELAY**

## UPS, Inverter, Control panel, Voltage stabilizer

### HF3FA (215)



- 1 pole: 15A 125VAC, 10A 250VAC/28VDC
- Product in accordance to IEC 60335-1 available

### HF3FF (215)



- 1 pole: 10A 277VAC/28VDC

### HF14FW(136)



- TV-8, 20A switching capacity (1 pole configuration)
- 4kV dielectric strength
- Meeting VDE 0700, 0631 moisture insulation

## UPS, Inverter

### HF105F-1(136)



- 40A switching capability
- 4kV dielectric strength (coil to contacts)
- Unenclosed, Plastic sealed and dust protected types available

## Railways and Air-con.

### HF102F



- Heavy load up to 5000VA
- Ideal for motor load (65A High inrush current)
- PCB & QC layouts available

## Timers/Relay module

### HF33F



- 1 pole: 10A 125VAC, 5A 250VAC/30VDC
- Creepage distance: 8mm (NC to NC)
- High sensitivity 200mW available

## Lighting application

### HF46F



- 1 pole: 5A 277VAC/30VDC at 85°C
- Surge withstand voltage up to 10kV
- High sensitivity: 200mW

## UPS

### HF115FD



- 16A switching capability
- Creepage distance: 10mm
- Updated version of HF115F
- 1 pole equipped with automatic production line

## PLC Controller

### HF49FD



- 3kV dielectric strength between coil and contacts
- Slim size: width 5mm, height 12.5mm
- High sensitive: min. 120mW

## Air-con.

### HF118F(136)



- 1 pole: 10A, 28V (2 pole): 5A
- dielectric strength: 5kV
- Creepage distance >8mm
- Reflow soldering available

## Telecom, EPABX, Mobile tower

### HFD27



- High contact capacity 2A 30VDC
- Matching 16 pin IC socket
- Epoxy sealed for automatic-wave soldering and cleaning

### HFD23



- 1 Form C configuration
- 2A switching capability
- High sensitive: 150mW
- Plastic sealed type available

### HFD3



- Surge withstand voltage up to 2500VAC, meets FCC Part 68 and Telcordia
- SMT and DIP types available
- Single side stable and latching type available

## Control panel



### HF18FF / HF18FH

- 7A switching capability (2C, 3C type)
- Various terminals, test button available
- Gold plated contact available
- 2 to 4 pole configurations



### HF13F

- 15A switching capability (1 Form C)
- Conform to the CE low voltage directive
- 1 & 2 pole configurations
- Various terminals available

AUTHORISED DISTRIBUTOR: \_\_\_\_\_



**MILLENNIUM SEMICONDUCTORS**

[www.millenniumsemi.com](http://www.millenniumsemi.com)

Corporate Office: 17/18/19, 2nd Floor, Mahaxmi Heights, Mumbai-Pune Road, Pimpri, Pune 411 018, Maharashtra, INDIA.  
Tel.: 91-20-27484800, 27484900/27485000, 9921107771. Fax: 91-20-27421485, Email: kshitiq@millenniumsemi.com



EN ISO 9001  
Certificate Reg. No. 25130 92034187  
since July 01

Branch Offices: • Ahmedabad • Bangalore • Chennai • Coimbatore • Delhi • Hyderabad • Mumbai