

ment range of -50°C to 2250°C (-58°F to 4082°F) and DS ratio of 50:1. Its spectral response is 8µm to 14µm and adjustable emissivity 0.1 to 1.0. This meter is supplied with a user manual, 9V battery and a carrying case. It has application in steel and metallurgical industries.

Kusam Electrical Industries Ltd, Mumbai

Phone: (022) 24156638

E-mail: sales@kusam-meco.co.in

Web: www.kusamelectrical.com

Single-phase electricity meter

Maxim Integrated Products has introduced ZON M3 (MAX71315) single-phase electricity meter. It integrates four 24-bit ADCs for 4-channel data collection and ±0.1 per cent measurement accuracy over 5000:1 dynamic range. Its 32-bit metrology compute engine (CE) ensures high-accuracy processing of collected data. Its two touch switch inputs eliminate mechanical switches and improve user experience, and its infrared communications interface eliminates the typical extra IR receiver module. Its high integration reduces cost and improves user experience.

Maxim Integrated Products, Inc., Bengaluru

Phone: (080) 30285800

E-mail: sales@maximintegrated.com

Web: http://www.maximintegrated.com/

Single-function temperature calibrators

Fluke Corp. introduces two single-function calibrators for simulating process temperature sensors. Fluke 712B RTD and 714B thermocouple temperature calibrators allow instrument, process and plant maintenance technicians to quickly and easily test process temperature instrumentation. The Fluke 712B measures and simulates

13 different resistance temperature detector (RTD) types and resistance, and the 714B measures and simulates 17 different thermocouple types as well as millivolts, to verify process sensors by direct comparison of measured versus

reported temperatures.

TTL India Pvt Ltd (a Fluke company),

Mumbai

Phone: 1800-209-9110

E-mail: info.india@fluke.com

Web: http://www.fluke.com

Solder paste inspection equipment

Korean firm Pemtron launched its latest version of solder paste inspection equipment. It offers a reliable combination of 2D and 3D inspection with automatic zero point setting for accuracy. The equipment comes with Pemtron's patented composite colour image processing technology which offers simple inspection management and programming along with the option of a barcode reader. It is a low-cost and low-maintenance system as it is made up of standard spare parts that are easily available in the market.

Kyoritsu Electric India Pvt Ltd, Thane

Phone: (0250) 2024668

E-mail: sales@kyoritsuelectric.com

Web: www.kyoritsuelectric.com



COMPONENTS

High-power ultra-low-ohmic shunt resistors

ROHM Semiconductor has announced the development of high-power ultra-low-ohmic shunt resistors ideal for current detection in applications with increased power requirements, such as automotive systems and industrial equipment. The new PSR series includes PSR400, which is rated at 4W, and PSR500, guaranteed up to 5W. Key features include exclusive precision welding technology utilised for improved rated power (5W) and superior temperature coefficient of resistance, even in the ultra-low-ohmic region.

ROHM Semiconductor India Pvt Ltd, New Delhi

Phone: (011) 41777050

E-mail: niranjan@rohm.com.sg

Web: www.rohm.com

Radial-leaded varistors for automobiles

Littelfuse has introduced the AUMOV series of low-voltage, high-surge-current, radial-leaded varistors for automotive applications. It offers 50 per cent greater surge with standing capability than existing technologies in the market for low DC voltage applications. The maximum peak surge current is rated up to 5kA (8/20µs pulse) to protect sensitive automotive systems from transients induced by load dump, jump starts and other transient events. Its compliance with the AEC-Q200 automotive electronics industry standard makes it ideal for use in both the vehicle's passenger compartment and under-the-hood applications. The AUMOV series offers a wide voltage range of 16V DC to 50V DC and is available in five disc sizes such as 5mm, 7mm, 10mm, 14mm and 20mm.


Littelfuse, Inc., Noida

E-mail: wvinaik@littelfuse.com

Web: www.littelfuse.com

Optical transceiver IC

Maxim Integrated Products has launched MAX3956 10GBASE-LR SFP+ optical transceiver IC to achieve high performance in optical modules with low power consumption. Optical module designers must typically trade high performance for power consumption in their applications. The MAX3956 SFP+ laser transceiver IC solves that problem. It delivers better than 50 per cent



transmit mask margin performance (1k waveforms, zero mask hits) with <0.8W total SFP+ module power dissipation. This reduced power dissipation lowers operational expenditures and improves thermal reliability in data centres.

Maxim Integrated Products, Inc., Bengaluru

Phone: (080) 30285800

E-mail: sales@maximintegrated.com

Web: http://www.maximintegrated.com/