

Rubycon

RUBYCON CORPORATION

HIGH QUALITY & RELIABLE ALUMINUM ELECTROLYTIC CAPACITORS

Applications : UPS / Inverter / AC Drives / DC-DC Converters/
LED Drivers/ Power Supply Units



RUBYCON SINGAPORE PTE LTD (INDIA LIAISON OFFICE)

123, Dimple Arcade, Thakur Complex, Kandivali East, Mumbai - 400101
Tel: 022-28543154; Fax: 022-28543155, Mobile: 09820408945,
Email: chandramouli@rubycon.co.jp

SCREW TERMINAL TYPE

Temperature : 85°C/105°C
Life Hrs : 2000Hrs to 5000Hrs
Cap Value : 200uf to 68000uf
Voltage : 10V to 500V DC

SNAP-IN TYPE

Temperature : 85°C/105°C
Life Hrs : 2000 Hrs to 7000 Hrs
Cap Value : 22uf to 8200uf
Voltage : 10 V to 500V DC

RADIAL TYPE

Temperature : 85°C/ 105°C
125°C/130°C/150°C
Life Hrs : 2000Hrs to 20000Hrs
Cap Value : 1uf to 3300uf
Voltage : 6.3 V to 500V DC

SMD TYPE

Temperature : 105°C/ 125°C
Life Hrs : 2000Hrs to 5000Hrs
Cap Value : 1uf to 1000uf
Voltage : 6.3 V to 100V DC

www.rubycon.co.jp

Systellar
Innovations
Affordable Solar Power



Solar Charge Controller

- MPPT and PWM charge controllers
- High efficiency digital design - up to 98.5%
- Power Saver accessory converts normal inverter into Solar inverter
- Battery specific charging for Flat Plate/ Tubular/SMF Battery
- 4 Stage battery charging - Boost, Absorption, Float, Tickle charging
- User settable features using LCD display in MPPT models
- Overcharge / Short-circuit / Low battery / Reverse polarity protection
- Warranty- MPPT model - 2 years, PWM model - 1 year

Models
PWM : 12/24V 20 & 40 A
PWM : 50V to 240V 20A
MPPT : 12/24V 20 & 40 A
MPPT : 48V 20 & 40A

Solar LED Street Lights (9W - 50W)

- Microprocessor based PWM design
- Solar Panel dirty warning
- LED dimming option 4 or 6 hrs after sunset
- LED driver PCB with charge controller also available



Systellar Innovations

Shankar Chowk, Delhi Road, Meerut - 250002, U.P.
www.systellar.in | info@systellar.in | Contact: 9917080700, 0121-2400384

Dealer Inquiries Solicited

BE-106 BE-103 BE-104 BE-105

Warranty 2 Years

Constant Current LED Driver

MODEL NO.	BE 103	BE 104	BE 105	BE 106
Universal Input 85 VAC - 265 VAC	✓	✓	✓	✓
Short Circuit Protection	✓	✓	✓	✓
Over Load Protection	✓	✓	✓	✓
Thermal Shutdown	✓	✓	✓	✓
Efficiency	> 88%	> 85%	> 85%	> 85%
Active PFC	-	-	-	> 9.9
THD	-	-	-	< 15%
Range	8W-15W	8W-22W	15W-22W	15W-22W
Dimension (H/W/L, mm)	25/40/75	33/50/85	30/35/113	32/50/98

BE-102 3W - 6W

BE-101 1W - 3W

BRISK ELECTRONICS

Contact No.: 9867673752 / 9819673752
Email: briskelectronics1@gmail.com

Customised Drivers Available