

NEW PRODUCTS

RECENTLY INTRODUCED IN INDIA, FROM NEAR AND FAR

COMPONENTS

IGBT power module

Vishay Intertechnology Inc. has introduced four new IGBT power modules, designed specifically for string solar inverters and medium-power-range uninterruptible power supplies (UPS). They have combined ultrafast trench IGBTs, high-efficiency HEXFRED and FRED Pt diode technologies and thermistors for easy thermal management in single packages featuring pressfit technology.

Their integrated design helps designers reduce time to market and improve overall system performance. For 3-level NPC topologies, the VS-ENQ030L120S provides a collector-to-emitter breakdown voltage of 1200V and a collector current rating of 30A. Designed for 3-level inverter stages, the VS-ETF075Y60U and VS-ETP150Y65U offer designers a choice of 75A and 150A collector current ratings and 600V and 650V collector-to-emitter breakdown voltages, respectively, and provide high-temperature performance of +175°C. Optimised for double-boost converters, the 15A VS-ETL015Y120H features a collector-to-emitter breakdown voltage of 1200V, high-efficiency silicon boost diodes, integrated 62A bypass diodes and panel short-circuit full-current reverse polarity protection diodes. All devices offer a modular and scalable design to fit higher-power-level applications.

Vishay Components, Pune

Phone: 020-30516200

Website: www.vishay.com

Ambient-light and proximity sensor

STMicroelectronics has revealed a new, highly-accurate optical range-finding module based on FlightSense's time-of-flight technology that offers designers superior distance-measurement capa-



bility. It provides accurate distance sensing by measuring the time for emitted light to reflect back from the target.

ST's VL6180X module combines FlightSense proximity sensing with an ambient light sensor (ALS) and supports basic gesture recognition to simplify the user-interface design, while also offering enhanced performance. This device supports a wide range of creative use cases across multiple markets, including smartphones, tablets and game controllers, while also improving the performance of consumer appliances and industrial products.

The VL6180X module is offered in a compact 4.8x2.8x1.0mm optical LGA12 package and can accurately measure the distance of objects at up to 100mm or farther, subject to operating conditions. The module provides an I²C interface for host control and reading ranging or ambient light level results, as well as two programmable GPIO pins that can be configured to implement threshold applications.

STMicroelectronics, Noida

Phone: 0120-2352999

Website: www.st.com

TEST & MEASUREMENT

IR thermometer

FLIR Systems Inc. released its TG165 imaging IR thermometer—a powerful, affordable, compact tool that lets you see invisible heat patterns, measure temperatures accurately and conveniently store images and measurement data for reporting.



Built around FLIR's exclusive Lepton micro-thermal imaging camera core, the TG165

eliminates the blind guesswork of troubleshooting by combining a single-spot IR thermometer with the power of a thermal camera in a rugged, compact package. This speeds troubleshooting, making it easy to find invisible hot and cold spots from a safe distance so you can investigate and solve problems quickly.

Fast and easy to use, TG165 requires no training. Its dual lasers visually mark the edges of what is being measured and the crosshairs pinpoint the centre point of the measurement area. TG165 is designed to withstand a two-metre drop, making it rugged enough for industrial use.

FLIR Systems India Pvt Ltd, New Delhi

Phone: 011-45603555

Website: www.flir.com

Mixed signal oscilloscope

The new PicoScope 3000D series mixed signal oscilloscopes (MSOs) are ideal for engineers working on embedded systems. These USB-connected devices form a complete portable test system, with two or four analogue channels and 16 digital channels, as well as a built-in arbitrary waveform generator.

The PicoScope 3000D series MSOs are available with analogue bandwidths from 60MHz to 200MHz. Maximum digital input frequency is 100MHz, equivalent to a data rate of 200Mbps on each channel. All models come with USB 3.0 interface and are fully compatible with USB 2.0, giving high performance and fast update rates with both port types.

The series offers features such as maths channels, automatic measurements with statistics, spectrum analysis and colour-persistence display mode. Also built-in are advanced digital triggering with pulse width, window, dropout, channel logic, digital pattern and other qualifiers, mask-limit testing and alarms. Serial decoding supports SPI, I²C, I²S, RS-232/UART,