

CAN, LIN and FlexRay protocols on up to 20 analogue and digital channels, even with a mixture of protocols at the same time.

VigVen Tech Mark Pvt Ltd, Bengaluru

Phone: +91-80-23541313

Website: <http://vigven.com/products/pcusb-oscilloscope/mso/>

Tire pressure monitoring system

Freescall Semiconductor has introduced the FXTH87 tire pressure monitoring system (TPMS) family, which is the smallest integrated package TPMS solution available at an extremely light weight of 0.3 grams, enclosed in a 7×7×2.2mm package. The FXTH87 family is 50 per cent smaller than competing products, helping designers reduce the overall bill of materials costs. It provides low-power consumption, combined with the highest level of functional integration in one package, featuring a dual-axis accelerometer architecture, pressure and temperature sensor, integrated MCU, RF transmitter and low frequency receiver.

Its key features include a QFN 7×7×2.2mm package that enables visible solder joint for inspection, 100–450kPa and 100–900kPa pressure ranges, z-axis or dual xz-axis accelerometers, low-power wake-up timer and periodic reset driven by LFO, 8-bit MCU/S08 core with SIM, interrupt and debug/monitor, 512 bytes RAM/16k Flash, internal 315/434MHz RF transmitter, internal 125kHz LF receiver, six multipurpose GPIO pins (including two A/D inputs), among others.

Freescall Semiconductor, Noida

Phone: 0120-3950000

E-mail: anjali.srivastava@freescall.com

Website: www.freescall.com

LED LIGHTS

Floating lamp

ENRG, the emerging light, sound and storage products maker in India, announces the launch of one-of-its-kind floating or levitating lamps. These lamps work with the power of magnets, which keeps the upper half of the desk lamp



suspended in air. It also automatically rotates or spins mid-air, creating a whimsical sight, right in the middle of the living room.

Special features of these lamps include electromagnetic levitation and nine high-power LED modules. They generate a power of 100 to 240V, and come in a cool white colour.

ENRG Pvt Ltd, New Delhi

Website: <https://enrg.in/light/float-lamp.html>

Solar LED lanterns

Nearly 400 million people across India still do not have access to grid electricity. With the launch of these advanced off-grid solar solutions, the Tata solar Diva range of lanterns and table lamps (5L, 15L2 and 25L) as well as Tata solar Venus range of home lighting solutions (15L and 75L), people with no or limited grid access can now choose from a diverse and affordable range of products.



LED lights have an average lifespan of over 40 times that of CFL lights and use half the electricity. Tata Power Solar are using long-lasting, bright LED lights, offering high-efficiency, with the latest Li-ion/lead-acid battery technology combination to develop smart and efficient products. These new products are portable due to their light weight and ergonomic design, with multiple options including mobile charging facilities. In case of no/low sunlight days, products can also be charged through an AC.


Tata Power Solar

Phone: 1800 419 8777 (toll free)

Website: www.tatapowersolar.com

White LEDs

Toshiba has launched a series of ultra-compact devices that combine cost-effective gallium nitride-on-silicon (GaN-on-Si) chips with an industrial standard 3535 lens-type package. Devices in the TL1L3 series of 1.0W LEDs are supplied in a package with a footprint of 3.5mm×3.5mm and a height, including lens, of just 2.42mm. Despite their small size, the LEDs deliver typical luminous flux ratings of between 112 and 145 lumens.



The new TL1L3 LED series comprises seven devices offering colour temperatures from 2700K to 6500K. Minimum colour rendering index (Ra) ratings of up to 80 contribute to natural-looking lighting across all target applications. A low typical forward voltage (VF) of just 2.85V (at a forward current of 350mA) helps to keep power consumption to a minimum.

High-performance white LEDs have been fabricated on expensive sapphire substrates using relatively small 100mm or 150mm wafers. Toshiba LETERAS LEDs, however, use a highly cost-effective GaN-on-Si process technology that allows GaN LEDs to be produced on 200mm silicon wafers. TL1L3 LEDs are rated for operating temperatures between -40°C and 100°C and have a maximum power dissipation of 3.4W. Additionally, they offer a very low typical thermal resistance Rth(j-s) from LED junction to solder point of only 5°C/W.

Toshiba India, Gurgaon

Phone: +91-98101 21489

E-mail: arun.kumar@toshiba-india.com

Website: www.toshiba.semicon-storage.com