

NEW PRODUCTS

RECENTLY INTRODUCED IN INDIA, FROM NEAR AND FAR

TEST & MEASUREMENT

Field intensity meter

Model KM 828 field intensity meter introduced by KUSAM-MECO has LCD display and over-range indication. It can inspect particular objects or devices that radiate low-frequency electromagnetic waves, for instance, power cables, computer monitors, TVs, audio-visual equipment, electromagnetic ovens or electrical installations. Its measuring range is 0.1-400mG, 1-4000mG, 0.01-40 μ T, 0.1-400 μ T with accuracy of $\pm(3\%rdg+3digits)$. The frequency range is 30Hz-400Hz and the sampling time is 0.5 second. It has an ergonomic design and a holster to protect the instrument and carry it conveniently. Powered by 9V battery, it can operate at 0-50°C (32-122°F) and bear a relative humidity of $\leq 80\%$ RH.

Kusam Electrical Industries Ltd, Mumbai
Phone: 022-24156638, 24124540
E-mail: sales@kusam-meco.co.in
Website: www.kusamelectrical.com

Mixed signal oscilloscope

Fanless operation, 1MPts of memory depth and a 1GSa/s real-time sampling rate—these are the key features of the new R&S HMO1002 mixed signal oscilloscope from Rohde & Schwarz. With a vertical sensitivity of 1mV/div and integrated 128k-point FFT, the instrument offers features that are exceptional in the three-figure price segment. Embedded developers, service technicians and users in the education sector can benefit from a

comprehensive range of functions and many features that make everyday work more convenient.

R&S HMO1002 can be expanded at any time from 50MHz to 70MHz or even 100MHz bandwidth by means of a simple upgrade option. Its fanless design ensures quiet operation and makes the instrument less susceptible to faults. The oscilloscope's anti-glare display takes up approximately 40 percent of the front-panel area and is easy to read. A logic probe can be connected to the front panel.

An integrated pattern generator enables professional embedded developers to program protocol messages at up to 50Mbit/s. The three-digit digital voltmeter integrated into the instrument makes it possible to perform voltage measurements simultaneously on both analogue channels, with two user-definable parameters each. The digital component tester helps service technicians check the functionality of capacitors, coils and semiconductor elements quickly and easily. Teaching staff in the education sector will find the education mode in the R&S HMO1002 especially attractive.

Rohde & Schwarz, New Delhi
Phone: 011-42535400
E-mail: rsindia@rohde-schwarz.com

Multifunction instrument

Pacific Electronics now introduces a product which is versatile and can be used in any electronics laboratory for doing experiments in analogue and digital circuits.

The instrument includes a 30MHz CRO (DSO optional), 3MHz function generator, 0-30V/1A regulated power supply, frequency counter, AC millivoltmeter, curve tracer, voltmeter, ammeter, fixed DC power supply (+5V, ± 15 V), AC sources (5V, 10V, 15V, 20V), eight logic level selectors and indicators, clock generator and BCD 7-segment display outputs.

It occupies only 300x450x450mm space, reduces need for multiple instruments occupying much more space and minimizes the inventory. It is priced at approximately half the price of all the 13 instruments included in it.

Pacific Electronics Pvt Ltd, Secunderabad
Phone: 040-27791139, 9848058904
E-mail: audiogen@usa.net
Website: www.pacificelectronics.in



Spectrum analyser and RF recorder

Signal Hound has introduced an affordable real-time spectrum analyser and RF recorder, BB60C, which is simple and compact to use. It has frequency range of 9kHz to 6GHz, an instantaneous bandwidth (IBW) of 27MHz and sweep speed up to 24GHz/sec. The BB60C has improved spurious-free dynamic range (SFDR) by 20dB, flattened the noise floor and band transitions by more than 8dB.

BB60C is USB-powered, eliminating the need for external power supplies. It is portable, more accurate, flexible and occupies less space. It is a compelling choice for a broad range of applications including intermittent interference hunting, manufacturing process control, spread spectrum signal analysis, process automation and remote spectrum monitoring.

DT Technologies Pvt Ltd
Phone: +91-44-60502200
E-mail: sales@dttechsolutions.com



POWER SUPPLIES

Smart power modules

Fairchild has developed the F5B70xxx series of advanced motion SPM 7 mod-

