



ules to help designers meet needs like high performance and compact solu-

tions for power motors under 100W worldwide, small electric motors like in dishwashers, air-conditioners and fans. These modules deliver industry-leading light-load efficiency up to 44%, robust on-module protection and superior thermal efficiency up to 12% better from junction to case. Additionally, the FSB70xxx series integrates an optimised gate driver for the built-in MOSFETs (using FRFET technology) to minimise EMI and losses, while also providing multiple on-module protection features including under-voltage lockouts, thermal monitoring, fault reporting and interlock function.

Its key features include high-performance inverter output stage for AC induction, brushless DC and permanent magnet synchronous motors, optimised for low electromagnetic interference, HVIC temperature-sensing built-in for temperature monitoring, separate open-source pins from low-side MOSFETs for three-phase current-sensing, active-high interface, works with 3.3V/5V logic, Schmitt-trigger input, HVIC for gate driving with under-voltage protection and interlock function, isolation rating of 1500Vrms/min.

Fairchild Semiconductor (India) Pvt Ltd, Pune
Phone: 91-20-4000-6333

Website: <http://www.fairchildsemi.com>

DALI power supply

GlacialPower has added the GP-DP004N-16V to its DALI product lineup. Outputting 200mA, it is enough for a full 64-device DALI network. Compatible with DALI standard IEC62386, the power supply takes universal AC input from 100V to 240V to provide constant voltage at 16V. With over-current and short-circuit protection, users are ensured safe power. The GP-DP004N-16V provides 200mA to the DALI bus.

DALI is the newest standardised lighting control system offering fine control, better lighting efficiency, logarithmic dimming and simplified topology for lighting networks. A DALI

network can have up to 64 independent devices, in up to 16 groups. Each DALI network needs bus power and the GP-DP004N-16V supplies this need with 200mA of current at 16V, enough to power a full DALI network (128mA) and have current left over to power DALI devices without integrated power supplies. As an established global standard, DALI products are inter-compatible with each other, making installing lighting control systems easy.

The GP-DP004N-16V is priced at ₹ 1740 (approx.)

GlacialPower, Taiwan

Phone: +886 2 2244-1227

E-mail: sales@GlacialTech.com

Website: www.glacialpower.com

COMPONENTS

Single-core microcontrollers

Introducing the powerful, single-core series for industrial real-time control design, Texas Instruments (TI) has launched the new C2000 Delfino 32-bit F2837xS microcontrollers (MCUs). These single-core MCUs are the first in the industry to offer four 16-bit analogue-to-digital converters (ADCs), enabling precision feedback in power control applications. They are pin- and software-compatible with the recently introduced dual-core C2000 Delfino F2837xD MCUs and help expedite development when scaling from higher-performance industrial control applications to mid-tier control designs.

The Delfino F2837xS MCUs are also the next-generation, single-core solutions for those using the preceding Delfino F2833x MCU series. Developers can utilise existing investments from the F2833x MCUs and transition to the software-compatible F2837xS MCUs, which provide greater CPU performance and more advanced analog and control peripherals.

Fully featured C2000 Delfino F28377S 32-bit MCUs (TMX320F28377S) are now sampling. Developers can evaluate the new Delfino MCUs using the Delfino F2837xD Experimenter Kit docking station

(TMDXDOCK28377D) for \$219, which includes the modular controlCARD (TMDXCNC28377D), or purchase the controlCARD separately for \$159.

Texas Instruments, India

Website: www.ti.com

Terminal block system

FCI has introduced the new NQ SMT wire-to-board spring clamp system as an extension of its terminal blocks portfolio. The clamp has a robust design, versatile modular system, secure electrical contacts, low wire insertion and high wire retention forces. Its user-friendly lever latch is engineered for effortless wire removal, while its compact industry-standard PCB design makes it a noteworthy space-saver.

With a low-profile 5.00mm height, the SMT spring clamp is highly ideal for LED devices and other compact applications, such as LED lighting modules. It is also suitable for consumer electronics, factory automation equipment and applications which require easy-to-use wire insertion and extraction methods. Two contact pitch sizes are available: 2.5mm with a current rating of 5A (150V) and 4.0mm with a current rating of 7A (300V). Both models are end-to-end stackable and feature 1 to 10 contact positions.

FCI OEN connectors, Cochlin

E-mail: fcioen@fcioen.com

Phone: 0484-4090871, +9198957 09609

Octal ultrasound pulser

The cost and size of ultrasound imaging machines can be reduced with the new STHV800 8-channel ultrasound pulser from STMicroelectronics. The proprietary SOI-BCD6 process technology enables the combination of low-voltage CMOS logic, precise analogue circuitry and robust power stages on the same chip, offering unprecedented level of integration. The monolithic, high-voltage, high-speed pulse generator with eight independent channels integrates a controller-logic interface circuit, level translators, self-biased high-voltage MOSFET gate drivers, noise-blocking diodes and high-power P-channel and N-channel MOSFETs for the output stages of each channel.