



STELLER PROVIDES
THE MOST

Versatile
BEST-IN-CLASS AND COST
EFFECTIVE LED LIGHTING
PRODUCTS



Dealer &
Distributors
Enquiry
Solicited

LED Products And Solutions For Home And Commercial Applications



Industrial Light



Frameless Panel Light



3D Downlights



Bulb 270 Beam Angle



Tube Light



Underwater Light



Integrated Solar
Street Light



Solar Lanterns



Solar Inverter
upto 15KVA

FEATURES

SAVE 80%
ENERGY

Surge -4KV

Operational
Voltage:
AC 90-300V

Experience of
year in
Electronics
Industry



STELLER LED
SAVE ENERGY FOR A BRIGHTER FUTURE

Steller Electronics Pvt. Ltd.

(An ISO 9001:2008 Certified company)

Works : 118, Industrial Area, Mehatpur, Dist. Una, Himachal Pradesh, 174315 India

Head Office : F-347, Lado Sarai, MB Road, New Delhi 110030, India

Tel: 011 29523445, Mob: +91 8826443111, e-mail: sales@steller.co.in, www.steller.co.in

MG Chemicals

One company.
Many solutions.



Adhesives
Brushes
Cleaners / Degreasers
Conformal Coatings
Contact Cleaners
Desoldering Braid

Dusters + Circuit Coolers
EMI / RFI Shielding
Epoxies
Flux + Flux Removers
Glass + Screen Cleaners
Lubricants
Potting + Encapsulation

Prototyping Materials
RTV Silicones by GE
Solder
Specialized Chemicals
Swabs + Wipes
Thermal Management

POLYURETHANE COMPOUND / DOMING RESIN FOR SOLAR APPLICATION
WITH COMPLETE DISPENSING AUTOMATION FROM DAI INC., USA



PROGRESSIVE ENGINEERS


20, Harichand Mill Compd., Next to Subodh Textiles, Off LBS Marg,
Vikhroli (West), Mumbai - 400 079. Phone : 022-27838611 /
25796760 / 32944289. Email : info@progressiveengineers.net
Website : www.progressiveengineers.net



ISO 9001:2008 CERTIFIED



Industrial Loads
Range : 1KW - 300KW



Low Ohmic Power Resistors
Open Frame Axial & PCB Mounting
Range : 0.001 - 1 ohms Power : 0.5 W - 3 W
Tolerance : ±5%, ±2%, ±1%



Resistors Adjustable / Fixed
(Silicone Coated)
Range : E 001 - 500 K Power : 0.5 W - 5000 W
Tolerance : ±5%, ±2%, ±1%




Resistors Ceramic Encased
Range : E 001 - 100 K
Power : 2 W - 50 W
Tolerance : ±5%



Resistors Aluminum Housed
Range : 0.1 ohms - 100 K ohms
Power : 5 W - 1000 W
Tolerance : ±5%



Dynamic Breaking Resistor
Range : E1 - 100 K
Power : 40 W - 10000 W
Tolerance : ±5%



Rheostat (Open / Covered / LSM)
Range : 0.5 ohms - 10000 ohms
Power : 0.1 Amp - 200 Amp



Potentiometer (Single / Gang Type)
Range : 1 ohms - 10 K ohms
Power : 25 W - 1000 W
Tolerance : ±5%

STEAD ELECTRONICS (INDIA) PVT. LTD.

Sales Office : 1681/20, Mangal Market, Bhagirath Palace, Delhi-110006

Ph. : 23865929, 23862576 Fax : 011-23867485

Regd. Office : 17 U.A. Jawahar Nagar, Delhi-7

e-mail : sales@steadresistors.com visit at www.steadresistors.com