

NEW PRODUCTS

RECENTLY INTRODUCED IN INDIA, FROM NEAR AND FAR

COMPONENTS

Reed proximity sensor

Standex-Meder Electronics announces its MK15-501 magnetically-operated reed proximity sensor for surface-mount device (SMD) mounting. It is ideal for position-detection in surface-mounted PCB assemblies, meter anti-tampering sensors and lid-detectors in household appliances, as well as heating, ventilation and air-conditioning due to its simple internal structure. It is available in two lead designs: straight leads for cutting and PCB slot mounting and bent SMD gull-wing leads used when the wire coming from a chip bends horizontally to make contact with a solder pad on a substrate.

With only 16x2.8x2.8mm size, the MK15-501 is excellent for low-power operations, requiring no external power for sensor operation. It is especially useful for magnetic systems requiring long operating distances with permanent magnets. Available in four operating sensitivities, it is also available for high-power switches. The sensors are supplied taped and reeled according to IEC 286-3, suitable for auto-placement. The magnetic pull-in sensitivity is divided into several AT classes at 5 AT steps each.

Standex Engraving India Pvt Ltd, Bengaluru
Phone: 08110415154

Website: klsanagod@standexmeder.com

Low-value chip resistors

ROHM has developed low-ohmic chip resistors optimised for current detection applications in compact equipment such as smartphones and wearable devices. The UCR006 series of ultra-compact (0.6x0.3mm/0.2x0.1-inch) thick-film chip resistors is offered in resistances as low as 100mΩ, providing



greater energy savings. These are also the first 0603-size(mm)/0201-size(inch) resistors in the industry to ensure a temperature range of -55 to 155°C in the low-ohmic region, and feature twice the rated power compared with competitor products in the same size, enabling support for a wide range of applications. This higher power handling capability in a smaller size makes them ideal replacements for larger 1005-size(mm)/0402-size(inch) resistors, contributing to further miniaturisation.

ROHM's latest series utilises new materials and a new structure to achieve class-leading low resistance (100mΩ) in a 0603-size(mm), thick-film design. In addition, heat dissipation is improved, and rated power is increased to 0.1W—twice that of conventional products. Operating temperature range has also been expanded in the low-ohmic region to an industry-best of -55°C to 155°C, enabling compatibility with a greater variety of applications. And unique laser trimming technology makes it possible to achieve a resistance tolerance of ±1% (F Class), which has been traditionally difficult to realise at low resistances. These new products have adopted the reverse-mount design utilised in the existing series in order to minimise resistance variations during soldering and ensure a temperature coefficient of resistance (TCR) between 0 and 300ppm/°C, which reduces resistance fluctuations due to temperature changes. This provides high-accuracy current detection required by today's high-performance devices.

ROHM India Private Limited, Bengaluru
Phone: 080-4149290, 41250811
Website: www.rohm.com

LED driver

GlacialPower has launched dual-mode GP-LC7028 LED driver powering LED lighting of 7W to 20W. Featuring constant-current or constant-voltage operation, the LED driver mode and power

output can be adjusted

to fit a variety of lighting and signage applications. Power input and output lines are connected via robust and easy-to-use clips.



The GP-LC7028 is almost like two LED drivers in one, with DIP switch for either constant-current or constant-voltage mode for enhanced functionality. It can be customised to specific LED-lighting needs with eight modes of constant-current (from 250mA to 700mA) and constant-voltage (from 12V, 24V and 28V) operation. For constant-current mode, 1V to 10V dimming and push dimming can also be enabled with a dimmer.

GlacialPower, New Delhi
E-mail: sales@glaciallight.com

High-power LEDs

Taiwan Semiconductor Lighting Company has launched 65 degree products for unique applications like floodlights, bay lights and automotive applications. With a 125/65 degree silicone lens, the A3535L-xxx2 and A3535M-xxNx2 LEDs feature high Tj 150, high brightness and efficiency, as well as a good lifetime.

Pine Valley, Bengaluru

Phone: 09871155223

E-mail: gopal@semileds.com

Website: www.tslc.com.tw



INFORMATION TECHNOLOGY

Development platform and Wi-Fi

Texas Instruments SimpleLink Wi-Fi CC3200 LaunchPad and CC3100 BoosterPack, a development platform and Wi-Fi device created for faster and easier implementation of solutions for the Internet of Things (IoT), is now available through element14.