

NEW PRODUCTS

RECENTLY INTRODUCED IN INDIA, FROM NEAR AND FAR

TEST & MEASUREMENT

Spectrum analyser

GW Instek has introduced a 3GHz spectrum analyser designed upon a new-generation platform.

The analyser provides a high frequency stability of 25 ppb (0.025 ppm)



and noise floor of -142 dBm (preamplifier 'on') as the high sensibility measurement base. The flexible selection among 58 RBW ranges, along with spectrogram and topographic features, enables GSP-930 to capture and display transient, drifting and hopping signals in detail. The mixture of frequency-domain and time-domain information facilitates tracing of RF signal variations over time.

The GSP-930 is equipped with various interfaces, including LXI, USB, RS-232 and GPIB (optional).

Good Will Instrument Co. Ltd

Email: india_marketing@goodwill.com.tw

Web: www.gwinstek.com

Solar module analyser

Solar module analyser Prova 210 from Taiwanese manufacturer Prova is now available in India. It is capable of I-V curve test, maximum solar power (Pmax) search by auto-scan (60V, 12A), and measurement of maximum voltage and maximum current at Pmax. The I-V curve can be viewed with a cursor.

The analyser can also measure voltage at open circuit and current at short circuit. Additionally, it has

functions like data logging to analyse solar power characteristics over a period of time, calculation of solar panel efficiency (in percentage), minimum power setting for alarm function and built-in calendar. The range for scan delay setting is 0-3000 ms, solar panel area setting 0.001-9999 metre² and standard light source setting 10-1000W/m².

Instruments and Machinery Sales Corporation, Mumbai

Fax: (022) 22678864

Phone: 22691733

4GHz oscilloscope

Rohde & Schwarz has launched a 4GHz high-performance oscilloscope with 20GSa/s sampling rate. The RTO1044 can handle different data interfaces up to data rate of 1.6



Gbps and can also be used to test fast clock signals up to frequency of 800 MHz.

It has a high sensitivity and measurement accuracy and can be used for typically low-amplitude (<1V) signals. Owing to the extremely low-noise front-end, the full measurement bandwidth of 4 GHz is available at even the smallest scaling (1 mV/div.). The 10GHz single-core analogue-to-digital converter provides a



good dynamic range (ENOB > 7 bits). The oscilloscope has a high acquisition and analysis rate of one million waveforms per second. The digital trigger system makes it possible to accurately pinpoint narrow glitches (down to 50 ps) and their origin.

Rohde & Schwarz, New Delhi

Fax: (011) 42535433

Phone: 42535400

Web: www.rohde-schwarz.co.in

TOOLS & EQUIPMENT

M2M deployable system

Kontron has introduced a machine-to-machine (M2M) deployable system that can operate in extended temperatures and industrial environments.

The KM2M806XT comes complete with application-ready middleware and supports M2M digital device connectivity. It is based on Intel Atom 600MHz processor. External USB port simplifies use of M2M SDKs provided by M2M independent software vendors. Sufficient storage is provided for M2M smart service applications, middleware and operating systems on the 4GB internal MicroSD card. The



built-in accelerometer, dual HDMI and HD audio support enable designers to implement movement tracking and intensive audio/video smart services features.

The system supports 802.11 b/g/n at 2.4GHz band and 802.11a at 5GHz band.