

Kontron Technology India Pvt Ltd, Bengaluru
 Fax: (080) 40831001
 Phone: 40831004
 Web: www.kontron.com

COMPONENTS

Modular device connector

Varicon Modular by Phoenix Contact allows power and signal transmissions to be combined in one connector. The key features of this modular, compact,



IP67 connector system include direct PCB connection and elimination of the panel mounting base.

The contact insert modules are touchproof throughout and can be keyed to prevent incorrect connection. The direct PCB 900 and 1800 connection saves you a complete jumpering level and enables controlled and space-saving assembly.

The modular contact inserts are available in two, six and eight positions with screw and direct PCB connections in signal. These can be combined to form any pin configuration from two to 40 poles. The range also includes four-, five- and seven-position power connectors up to 690V/70A in screw connection. These can take along maximum 16 control signals in one connector solution.

Phoenix Contact India Pvt Ltd, New Delhi
 E-mail: response@phoenixcontact.co.in
 Web: www.phoenixcontact.co.in

SMd power inductors

A series of high-efficiency shielded and non-shielded surface-mount power inductors such as signal transformer SC32-150 is now available from Digi-Key.

The wire-wound power inductors

are sized to industry-standard packages for ease of design. These support multiple profile heights within the same footprint. This minimises the chance of having to rework or respin the PCB when values may need to be changed, for example, from a non-shielded inductor to a low-EMI shielded inductor.

Consisting of 2700 standard part numbers, the inductors cater to a broad range of consumer and industrial power applications including test and measurement, automotive electronics and industrial process control.

Digi-Key

Phone: 000-800-100-1274

Web: www.digikey.in

Smart reset chips

STMicroelectronics has introduced a new generation of its Smart Reset chips. The chips provide a means of resetting 'frozen' gadgets.

The dual-assert STM6524 IC effectively prevents accidental resets. The single-assert STM6519 targets single-button electronic devices like tablets and e-readers, with a similar programmable delay reset.



In addition to a small package size, the devices implement a customisable extended input delay time, from 0.5 to 10 seconds, which increases flexibility and enables manufacturers to distinguish their products through specific user-interface settings. These also integrate a dedicated test mode, which improves device testability and slashes test costs.

STMicroelectronics Pvt Ltd, Greater Noida (UP)

Phone: (0120) 2352999

Web: www.st.com

Server chip

AMD has introduced Opteron 3200 Series processor that offers Web and cloud hosting server functionality from cheaper, desktop-like infrastructure. The processor is based on Bulldozer architecture. AMD claims that it offers 38 per cent better price-performance while consuming 19 per cent lesser power per core.

Opteron 3200 comes in four- and eight-core configurations, with 45W-65W power consumption, and 1333MHz, 1600MHz, 1866MHz memory speed. The 2.7GHz base frequency can go up to 3.7 GHz in AMD Core mode. It offers two DDR3 memory channels supporting ECC UDIMM. The Opteron also supports up to two DIMMs per memory channel. It has up to 32GB memory capacity. The total cache is 16 MB for eight-core and 8 MB for four-core.

The processor is shipping in platforms from MSI, Tyan, Fujitsu and Dell.

AMD India Pvt Ltd, Gurgaon

Phone: (0124) 4696 000

Fax: (0124) 4696 177

Web: www.amd.com/in

8-bit PIC microcontrollers

Microchip has announced the PIC12F(HV)752 family of 8-bit PIC microcontrollers (MCUs) that features analogue and digital peripherals. These MCUs can be used in battery charging, LED lighting, ballast control, power conversion and system control.

The MCUs feature an integrated complementary output generator peripheral that provides non-overlapping, complementary waveforms for inputs such as comparators and pulse-width modulation (PWM) peripherals, while enabling dead-band control, auto shutdown, auto reset, phase control and blanking control. Additionally, these feature 1.75 kB of self read-write program memory, 64 bytes of RAM, an on-chip 10-bit analogue-to-digital converter, capture-compare PWM modules, high-performance comparators (40ns