





Helio Optoelectronics Corporation
Taiwan

Power LEDs
1 watt/3 watt / COB -13/17 watt
Heli-Rebel / H-Lamp

AUTHORISED DISTRIBUTORS



ZMDI
The Analog Mixed Signal Company

Zentrum Mikroelektronik Dresden
AG (GERMANY)

IC for LED drivers with only 4 external components * Dimming Feature
* LED protection with NTC.
Models: ZLED 70xx series

AUTHORISED DISTRIBUTORS



3M
WORLD LEADER IN THERMAL MANAGEMENT

The tapes and pads have

- Excellent Thermal Conductivity
- Very Good Electrical Insulation
- No need for Heat Sink Paste or Compound
- Hyper-soft material



VELTRON ELECTRONIC DEVICES PVT. LTD.
52/c Chotani Bldg., 2nd Floor, Proctor Road, Grant Road (East), Mumbai 400 007 India
Mob: +91 99 207 988 48, Tel: +91 22 2861 1032 / 3242 0719
E mail: sales@veltronindia.com, Web Site: www.veltronindia.com,

AUTHORISED DEALER FOR



COMBICON / CLIPLINE / PLUSCON / INTERFACE / TRABTECH.



PROTECTOR
CONNECTORS/RESETTABLE & BLADE FUSES

INCAP LIMITED
ELECTROLYTIC CAPACITORS



GUARDIAN
CONTROLS LIMITED
INDUSTRIAL/AUTOMOTIVE & TELECOM RELAYS



ELECTRONIC CONNECTORS,
SWITCHES, RELAY SOCKETS
& ELECTRICAL PRODUCTS

CARBON FILM , METAL FILM
& CHIP RESISTORS.





COMPONENTS
7/B, Ahmed Mansion, Churnam Lane, Lamington Road, Mumbai-400 007.
Phone : 2387 2308 Telefax : 2388 2332 E-mail: bc@bccom.net



Industrial Loads
Range : 1KW - 3000W

Low Ohmic Power Resistors
Open Frame Axial & PCB Mounting
Range : 0.001 - 1 ohms Power : 0.5 W - 3 W
Tolerance : ±5%, ±2%, ±1%

Resistors Adjustable / Fixed
(Silicone Coated)
Range : E 001 - 500 K Power : 0.5 W - 500 W
Tolerance : ±5%, ±2%, ±1%

Resistors Ceramic Encased
Range : E 001 - 100 K
Power : 2 W - 50 W
Tolerance : ±5%



ISO 9001:2008 CERTIFIED

Resistors Aluminum Housed
Range : 0.1 ohms - 100K ohms
Power : 5W - 1000 W
Tolerance : ±5%

Dynamic Breaking Resistor
Range : E1 - 100 K
Power : 40 W - 1000 W
Tolerance : ±5%

Rheostat (Open / Covered / LSA)
Range : 0.5 ohms - 1000 ohms
Power : 0.1 Amp - 200 Amp

Potentiometer (Single / Gang Type)
Range : 1 ohms - 10 K ohms
Power : 25 W - 1000 W
Tolerance : ±5%

STEAD ELECTRONICS (INDIA) PVT. LTD.
Sales Office : 1681/20, Mangal Market, Bhagirathi Palace, Delhi-110006
Ph : 23865929, 23862576 Fax : 011-23867465
Regd. Office : 17 U.A. Jawahar Nagar, Delhi-7
e-mail : sales@steadresistors.com visit at www.steadresistors.com

APLUS SPEECH MELODY
RF IC & MODULE

LOW COST VOICE OTP IC DURATION
10 SECONDS TO 180 MINUTES

Re-recordable Voice Ic 10 seconds to 16 minutes

VOICE OTP PROGRAMMING TOOL AVAILABLE

Mantra & Shloka IC COB Custom Designed
Speech Voice Melody Ic-COB-KIT Available.

SIREN-ALARM-VOICE IC

ENGG KITS & PROJECTS

RF MODULES TX - RX - TR ASK - FSK - AV

Led Flasher, MCU with Speech & Melody,
Custom Design Asic etc.



APLUS INDIA



Ground Floor Bakul Bag, Vasundhara, Opp. Indian Bank,
S.V. Road, Santacruz (West), Mumbai - 400 054
Tel.: 022-2618 2082 / 2617 3575 Fax : 91-22-26118035
Mobile : 9833374818 Website : www.aplusindia.net
Email : sales@aplusindia.net / sms003@sms033.com