

Soar to New Heights with RX 32-bit Extreme Performance MCUs



The RX600 series of 32-bit microcontrollers delivers both industry-leading 1.65 DMIPS/MHz performance and rich connectivity. Expand your choices with the genuine advantages of the extensive RX600 lineup with the revolutionary RX core.



Class-leading power and efficiency — bolstered by the industry's fastest embedded Flash memory. The highly scalable RX600 series addresses the demands of industrial, consumer and OA applications with high-speed, high-efficiency program processing.

Advanced Features

■ Extremely high calculation performance

- 165 DMIPS at 100 MHz CPU frequency
- 2.34 CoreMark/MHz from Flash (EEMBC certification)

■ Extremely wide connectivity support

- Up to 2 ch of USB 2.0 (Host/Device/OTG)
- Ethernet MAC 10/100 Mbit with DMA support
- Up to 3 ch of CAN 2.0B compliant interfaces
- Up to 13 ch of SCI, 4 ch of I²C and 3 ch of SPI interfaces

■ Extremely wide platform concept

- 48 to 177 pin package options (LQFP, LGA and BGA)
- Embedded 32 KB to 2 MB Flash (Zero Wait Flash Technology)

■ Extremely low power consumption

- 0.5 mA/MHz with all peripherals active

■ Enhanced safety and peripheral functions

- Meets IEC 60730 Class B (fail-safe) safety standard for home appliances