

AC-DC front-end power module

Vicor Corporation has introduced the VI BRICK AC front-end module for high-density, high-efficiency AC-to-DC power conversion. This new module is a complete AC-DC converter that operates over the universal AC input range of 85-264V to deliver a fully isolated and PFC-regulated 48V output.



In a low profile package measuring 95.3x48.6x9.5 mm³, the module provides a power conversion density of 7.5W/cm³ or 3.3W/cm³ for a complete supply that includes all the necessary components including hold-up capacitance.

The module is compatible with a variety of downstream DC-DC power conversion components including Vicor's portfolio of high-density, high-efficiency VI Chip and VI BRICK converters.

Vicor India, Bengaluru
Phone: (080) 41468665
Web: www.vicorpower.com

COMPONENTS

32-bit microcontrollers

Fujitsu Semiconductor Asia Pte Ltd has launched FM4 family of 32-bit general-purpose RISC microcontrollers based



on ARM Cortex-M4 processor core. The new microcontrollers cover high-end product range, featuring higher

performance and enhanced functionality with digital signal processing and floating-point number processing unit.

While maintaining the abundant peripheral functions of FM3 family, FM4 family adds SDRAM and SD card interface functions and an expanded package line-up. The family also features a wide range of timers and serial communication functions—all supplied with flash technology.

Fujitsu Semiconductor Asia Pte Ltd, Bengaluru
Fax: (080) 28416660
Phone: 28419990
E-mail: sales.fsal@sg.fujitsu.com
Web: www.fujitsu.com

4MB flash memory device

Texas Instruments (TI) claims to have introduced the industry's first high-temperature, non-volatile Flash memory device for harsh environments.



The SM28VLT32-HT has an operational capacity of 4 MB and eliminates the need for costly up-screening and qualification testing of industrial-grade components for temperature ranges outside datasheet specifications. It allows data logging at extreme temperatures and is guaranteed for at least 1000 hours of operating life in harsh environment applications, including oil and gas exploration, heavy industrial and avionics.

The SM28VLT32-HT is sampling now in an 8x25mm² ceramic flat pack.


Texas Instruments (India) Pvt Ltd, New Delhi
Phone: 1-800-425-7888 (toll-free)
Web: www.ti.com

MISCELLANEOUS

Electronic housings

Phoenix Contact has launched CombiCon Housings for electronic devices. CombiCon Housings comprise different kinds of enclosures, panel-mounting base and accessories for application in the field of industrial electronics.

These electronic housings install quickly on a common 35mm DIN rail. Apart from a few exceptions, the



connecting terminal blocks can be fitted and machine-soldered during PCB assembly. If a device cannot be installed on the standard DIN rail directly, mounting plates are available for adaptation.

Phoenix Contact India, New Delhi
Fax: (011) 26383285
Phone: 30262800
E-mail: response@phoenixcontact.co.in
Web: www.phoenixcontact.co.in

Digital school broadcast system

WS Telematics has launched a micro-processor-based digital school broadcast system. The system is based on



digital switching technology, unlike the electromechanical technology used in conventional school broadcast systems. This makes the system very compact and easy to manage and maintain. It allows an announcement to be made from different locations. For this, only an extension communication instrument is required, rather than replication of the entire school broadcast console as in the case of a conventional system.

WS Telematics
E-mail: ustelematics@gmail.com
Web: www.ustelematics.com