

Five Stars: Ultra Compact Low Profile AC/DC Power Supply

RECOM's AC/DC Power Modules Exceed Worldwide Standby Power Standards

- ✓ Ultra-low 30mW Standby Power Consumption
- ✓ 1 Watt through 6 Watt PCB Mount Package
- ✓ Extra Wide Input Voltage Range (90 ~ 277VAC)
- ✓ Class II Power Supply with 3kVAC Isolation
- ✓ -25°C to +85°C Operating Temperature
- ✓ Low Output Ripple
- ✓ Short Circuit Protected Outputs
- ✓ UL, EN and CE Certified
- ✓ Single or Dual Output Options



The new RAC series:
Ultra-low power consumption
to meet the European EuP
guidelines.

No-load consumption score chart		
Five stars= most energy efficient		
★★★★★	≤0.03W	
★★★★	>0.03W to 0.15W	
★★★	>0.15W to 0.25W	
★★	>0.25W to 0.35W	
★	>0.35W to 0.5W	
no stars	>0.5W	
Source: Energy Star		

The RAC01 and RAC02 have a miniscule no load power consumption of only 30mW, while the RAC03 uses less than a tenth and the RAC06 only half of the standby energy specified in the existing EPA Energystar, CEC, CECP and the European EuP guidelines. This ultra-low power consumption means that the converters will still comfortably meet the future standby consumption limits of 500mW when the standards are revised in 2013.