

Microcontrollers

Offering total system power savings for co-processor designs, Texas Instruments Incorporated (TI) has announced MSP430F521x/F522x microcontroller family. These microcontrollers support a main supply rail (1.8V-3.6V) and an input/output supply rail (1.8V±10 per cent), eliminating the need for level



translators and offering system-level advantages such as reduced system cost and increased flexibility.

Featuring dual-voltage rail capability, the microcontrollers can operate as an ultra-low-power co-processor to higher power/performance devices such as TI's OMAP processor and Sitara platforms.

Texas Instruments (India) Pvt Ltd, New Delhi
Phone: 1-800-425-7888 (toll-free)
Web: www.ti.com

30A fully-encapsulated power module

Intersil Corporation claims to have introduced the industry's first 30A fully-encapsulated power module. Featuring a high power density, IS-L8225M simplifies the design of high-performance board-mounted power



solutions. It can deliver up to 100W output power from a small 17mm² PCB footprint.

The two 15A outputs may be used independently or combined to deliver a single 30A output. Current sharing

and phase interleaving allow up to six modules to be paralleled for 180A output capability. High efficiency and low thermal resistance permit full power operation without heat-sinks or fans.

Intersil Corporation, Bengaluru

Fax: (080) 41121035

Phone: 30428400

Web: www.intersil.com

MISCELLANEOUS

Flex-ATX motherboard with AMD R-Series APU

Kontron has introduced a feature-packed embedded Flex-ATX motherboard based on the new AMD Embedded R-Series accelerated processing unit (APU) and AMD A75 controller hub.



KTA75/Flex is designed for graphics-intensive and highly parallel embedded computing applications and provides long-term stability and reliability due to its board layout with long-term stable solid capacitors.

With integrated discrete-class AMD Radeon HD 7000 Series graphics, it delivers 3D/HD graphics and accelerated processing capabilities together with the ability to drive up to four displays simultaneously—either as independent displays or as a single large surface.

Kontron Technology India Pvt Ltd, Bengaluru

Fax: (080) 40831001

Phone: 40831004

Web: www.kontron.com

LED floodlight

GlacialLight has added GL-FL60—a 60W AC-input LED floodlight with Philips Lumileds LED chips—to its energy-efficient LED floodlight series. GL-FL60 provides bright and pleasing illumination suitable for indoor and outdoor retail, commercial and industrial lighting applications. It can accept a

wide range of AC voltages—from 100 to 277 volts—making it suitable for a variety of operating environments. Its ability



to operate in a wide range of temperatures (−20°C to +40°C) and IP66-certified water-resistant design mean it can be used in nearly all weather conditions.

GL-FL60 is sold in two different versions with varying beam angles: 20° for spot-light applications and 60° for floodlight applications.

Lotus Insulation Services

E-mail: kalekarsn@gmail.com, sales@lotusin.co.in

Single-output switching power supply

Nuteck Products has launched a 120W single-output switching power supply. Offering a wide input supply range, it



has a low leakage current of less than 1 mA. It can also withstand 440VAC continuous input and is 100 per cent full-load burn-in tested. Other features include high efficiency, long life and high reliability along with miniature size and high power density.

Nuteck Products, Pune

Phone: (020) 26811161/2

E-mail: rajesh@nuteckproducts.com

Web: www.nuteckproducts.com