

NEW PRODUCTS

RECENTLY INTRODUCED IN INDIA, FROM NEAR AND FAR

COMPONENTS

H.264/MPEG-2 transcoders

Fujitsu Semiconductor has introduced bidirectional H.264/MPEG-2 transcoders that can convert both video and audio data, and also perform full-HD (1920x1080) conversions. With built-in memory, these consume 1.2 watts.



The MB86M01, MB86M02 and MB86M03 transcoders are equipped with a transrating function that enables H.264 video data to be converted into higher-compression H.264 video data. The MB86M01 and MB86M03 measure just 13 mm², while the MB86M02 comes in a 21mm² package.

Fujitsu Semiconductor Asia Pte Ltd,
Bengaluru

Fax: (080) 28416660

Phone: 28419990

Web: www.fujitsu.com

Real-time clock/calendar devices

Microchip Technology has introduced a family of standalone real-time clock/calendar (RTCC) devices. The MCP-795WXX/BXX RTCC devices feature millisecond alarms and a 10MHz serial peripheral interface.



The devices include an electrically erasable programmable read-only memory, a static random-access memory and a unique ID—which can be ordered blank or with a preprogrammed MAC address. Along with the automatic battery switch-over for backup power, the devices also have a power-fail time stamp.

Microchip Technology (India) Pvt Ltd, New

Delhi

Fax: (011) 51608632

Phone: 41608631

Website: www.microchipdirect.com

Ethernet PHY chips

Renesas Electronics has released two single-channel Ethernet physical layer (PHY) devices for industrial communication systems.

The Ethernet interface of the devices is fully-compliant with IEEE 802.3/802.3u for 100BASE-TX,



100BASE-FX and 10BASE-T, and supports IEEE 802.3u auto-negotiation and parallel detection, and full- and half-duplex operation.

The μ PD60610GA-GAM-AX and μ PD60611GA-GAM-AX are available in 48-pin, 0.5mm pitch, 7x7mm² quad flat package.

Renesas Electronics Singapore Pte Ltd,

Bengaluru

Fax: (080) 67208777

Phone: 67208700

Web: www.renesas.com

Voice recording ICs

APLus has launched two series of ICs for voice recording and playback ap-

plications. The VIR3K and aIVR series are one-time-programmable voice ICs embedded with an 8-bit microcontroller and memory.

The VIR3K10, VIR3K21 and aVIR3K42 support voice recording for 10, 21 and 42 seconds, respectively. The series supports Windows XP and USB programming.

The aVIR1004, aVIR2104, aVIR4208, aVIR8511 and aVIR341N support voice recording for 10, 21 and 42, 85 and 341 seconds, respectively.

APLus, Mumbai

Phone: (022) 26182082, 26173575

Integrated transceiver devices

ON Semiconductor has introduced integrated transceiver devices for use in local interconnect network (LIN) designs in automotive and industrial applications.

The NCV7425 LIN+LDO transceiver features integrated voltage regulator and reset functionality. The LIN version 2.x /SAE J2602 device interfaces between a LIN protocol controller and the physical bus, and supports transmission rates of up to 20 kbps. Available in 3.3V and 5V output options, the NCV7425 supports up to 150mA loads, bus voltage of $\pm 45V$ and offers on-board functions that include thermal shutdown, indefinite short-

