

circuit protection, load-dump protection to 45V and electrostatic discharge protection up to ± 10 kV.

Arrow Electronics India Pvt Ltd, Noida

Fax: (0120) 4535505

Phone: 4535500

Web: www.arrowasia.com

TEST & MEASUREMENT

Embedded controller

National Instruments (NI) has introduced a real-time (RT) embedded controller that is designed specifically for deploying embedded real-time measurement and control applications.



The PXIe-8100 RT features 1.66GHz Intel Atom D410 single-core processor, 512MB standard RAM and 667MHz DDR2 memory.

The controller includes a 10/100/1000BASE-TX Ethernet port, two USB 2.0 ports and an RS-232 serial port. It also features 51kHz single proportional-integral-derivative loop rate.

NI Systems (India) Pvt Ltd, Bengaluru

Phone: (080) 41190000

E-mail: ni.india@ni.com

Safety testers

GW Instek has introduced GPT-9800 series safety testers that are claimed to meet safety standards such as IEC, EN, UL, CSA, GB and JIS. The series includes four safety testers—GPT-9804, GPT-9803, GPT-9802 and GPT-9801. The testers are equipped with a panel layout, a high-resolution dot-matrix LCD and colour LED indicators



for measurement results. Test functions include AC withstanding (5kV AC/40mA), DC withstanding (6kV DC/10mA), insulation resistance (50V-1000V DC) and ground bond (30A AC maximum) tests.

Other features include 100 sets of memory to save panel settings, on-off terminal in the front panel, a signal input/output port in the rear panel, and RS-232C, USB and GPIB (optional) interfaces.

Good Will Instruments Co. Ltd, Noida

E-mail: india_marketing@goodwill.com.tw,

marketing@goodwill.com.tw

Web: www.gwinstek.com

Pocket analysers

POWER 2U Technology Solutions has introduced BitScope pocket analysers that combine a powerful mixed-signal oscilloscope, protocol analyser, waveform and clock generator, spectrum analyser and data recorder in a single USB-powered device.

The analysers offer ten capture channels (two analogue and eight



digital) with 11MHz analogue bandwidth, 40MSps logic speed, up to 12-bit analogue resolution and frame rate of 100 Hz. Other features include serial peripheral interface, CAN, UART packet decoders, X-Y phase plotter and data recorder.

POWER 2U Technology Solutions, Sydney

E-mail: power2u.technology@gmail.com

Multifunction power and energy monitor

Meco Instruments has introduced a multifunction power and energy monitor (MFM-144x192UMT) that simultaneously displays four parameters in four rows and has energy retention and password-protected energy reset facility.

The monitor indicates total root-mean-squared measurements with



64 electrical parameters on 22 pages at three-phase and system measurement voltage, current, active/reactive/apparent power, frequency,

power factor and active/reactive/apparent energy.

Meco Instruments Pvt Ltd, Mumbai

Fax: (022) 27673310, 27673330

Phone: 27673311-16

E-mail: haren@mecoinst.com

Web: www.mecoinst.com

LIGHTING

LED high-bay lights

Laaj Lightings has launched LED high-bay lights with inbuilt fan for temperature control.

The lightings have a 110V-250V AC, ± 50 Hz power source and power factor greater than 0.90. With colour rendering index of more than 80 and driver efficiency of 85 per cent or more, the lightings come in 50, 70, 90 and 120



wattages. Housed in aluminium die cast, these mercury-free lightings have a life of 50,000 hours.

Laaj Lightings, Kolkata

Fax: (033) 24986878

Phone: 24986857

E-mail: info@laajlightings.com

Web: www.laajlighting.com

LED cap lamp

Kwality Electronics has introduced a high-power white LED cap lamp that has an inbuilt maintenance-free 3.7V,