


Miniature SMD Converter 100° C without derating

- ✓ Full power at 100 C ambient temperature
- ✓ 1kVDC or 3kVDC isolation options
- ✓ Class A EMC filter integrated
- ✓ Ideal for vapour-phase soldering
- ✓ Optional continuous short circuit protection
- ✓ UL/EN 60950-1 certified
- ✓ EN 60601-1 certified



The family of 0.25W, 1W and 2W SMD converters are designed to work at ambient temperatures of up to +100°C without derating. The unconventional enclosed open frame design in the series has been developed for fully automated manufacturing, and can easily withstand soldering temperatures in excess of +245°C. The new low EMC radiation converters are insulated for up to 3 kVDC, and are designed for voltages of between 3.3V and 24V; at just one gram in weight, the converters are insensitive to shock and vibration.



Designed specifically for
vapour-phase soldering...

RECOM

Authorised Indian Representative :



#782, 3rd Main, 1st Cross, 5th Phase, BEML Layout,
Rajarajeshwarinagar, Bangalore 560 098 INDIA.
Tel : 080 - 2861 1874, 2861 1950 Fax : 080 - 2861 1867

E-mail : info@omniscientelectronics.com, techsupport@omniscientelectronics.com

Web : www.omniscientelectronics.com

Branch Office:

AHMEDABAD

ahmd@omniscientelectronics.com

CHENNAI

chnsales@omniscientelectronics.com

DELHI

delhisales@omniscientelectronics.com

MUMBAI

mumbai@omniscientelectronics.com

PUNE

pune@omniscientelectronics.com

SECUNDERABAD

hyd@omniscientelectronics.com