



ATTENTION

LED Light Manufacturer

Channel Patti For LED Strip

Housing for Tube Light

Housing for Concealed Tube & Casing for T-5

Housing for Wall washer

Housing for LED PLL tube

Panel Light Housing

Round Panel Light Housing

Street Light Housing

SMPS For LED Strip

Housing for Flood Light

Our Product Range Consist of the following

- T8/T9 Dotted Lens/Lens for street light, 1 watt lens.
- Heat Sink for T8/T9
- Channel Patti for Epoxy.
- Panel Light Housing.
- Street Light Housing - 12 watt to 250 watt
- Tube Light Housing - T-5/T-8, T-10
- Wall Washer Housing - Ultra Thin, Heavy duty.
- Housing for LED PLL Light & Casing for T-5 Tube Light.
- Flood Light Housing : 30w,50w,60w,90w.
- Led Drivers : 1w-50watt , SMPS for LED Strips.

CALCOM TELELINK PVT. LTD.

Shop No.: 4-A, Plot No. 201, Road No. 13, Javahar Nagar, Goregaon (W) Mumbai - 62 (INDIA)

Telefax : +91-22-26760152

Cell : 9820976362/9820973320.

Email : Calcomteleshop@yahoo.com

Robotic Arm

I have successfully assembled the 'Robotic Arm' project published in November 2011 issue. Thanks to the EFY team!

Ashwin Mathew

Through e-mail

□ The 'Robotic Arm' project does not include the driver circuit for servo motors. Will the servo motors get sufficient current from the PIC microcontroller? Again, if the servos are working fine, will these not cause loading problem to the PIC microcontroller?

Nishant Mittal

Facebook

The author Venkat Raju replies:

The circuit is provided with three pins for connections to +5V, GND and PWM. Voltages for the servos are supplied from external regulators and current is also driven from the same. But each servo action is controlled through a pulse-width-modulated (PWM) signal generated by the microcontroller. Inside a servo motor there is a small comparator circuit that tries to match the PWM signal to the potentiometer value, which is attached to the shaft and drives the motor shaft accordingly. There is no load applied to the PIC microcontroller due to this.

Source Code Listing

While providing source code listing, e.g., movm.c in 'Moving Message Display on LCD' construction project on page 100 in EFY Dec. 2011 issue, it would be better if:

1. The source code is indented and formatted for at least 80 column-width (no line wraps)

2. Language keywords are colour-highlighted

Free editors like Vi and Notepad++ will let you do this without much hassle.

Jagmeet Singh Hanspal

Through e-mail

Data Acquisition

I am working on a project for bedridden patients that can be used to monitor pressure at various points in their body which are most vulnerable to bed sores. I have come across 'Eight-Channel Data Acquisition & Logging System' project published in April 2010 issue. Please suggest whether this system can be used in my project.

Jashin Kumar

Through e-mail

The author Devesh Samaiya replies:

You can easily modify the mentioned project as per your requirement. All you need is to find suitable calibration values and modify the following lines in the code:

```
temp=(ADC)*(48);
temp=temp/10;
temp=temp-2280;
temp=temp/10;
```

I calibrated it to display temperature (using LM335). You will have to find a suitable calibration procedure for your sensors by hit-and-trial method.

Solar-Powered Project

Please publish a do-it-yourself solar power project that supports air-conditioning during summers to avoid heavy electricity bills.

Baiju G.

Kozhikode

Job Portals

I am pursuing B.Tech in electronics and communications engineering. I would like to know which field offers good job prospects in embedded systems, very-large-scale integration and signal processing.

Jagadeesh Kumar

Through e-mail

EFY: You may check various job portals to know which field offers maximum opportunities for this skillset. You may also check our jobs portal www.jobs.electronicsforu.com and read career related articles on www.electronicsforu.com/electronicsforu/articles/