

```

convolution=imfilter(a,h);%PERFORM CONVOLUTION OPERATION
imwrite(convolution,'C:\efytest\efy.jpg');%%%%%%%%% ENTER
THE PICTURE LOCATION WHERE THE EDITED PICTURE IS TO BE STORED
HERE%% %%%%%%%%%%
new=imread('C:\efytest\efy.jpg');%%%%%%%%%
%% ENTER THE PICTURE LOCATION OF THE EDITED FILE HERE%%%%%%%%%
%%%%%%%%%
new1=rgb2gray(new);
averaging1=graythresh(new1);
bw1=im2bw(new1,averaging1);
[L1,num1]=bwlabel(bw1,8);
detectedobjects1=regionprops(L1,'all');

i1=0;

for j1=1:num;
if (detectedobjects1(j1).Area)>2500;
    i1=i1+1;
end
end
imshow(a);

ji=sprintf('%f',i1);
%set(handles.edit1,'string',ji);
%set(handles.text1,'string',j1);
% --- Executes on button press in pushbutton2.
function pushbutton2_Callback(hObject, eventdata, handles)
% hObject handle to pushbutton2 (see GCBO)
% eventdata reserved - to be defined in a future version of
MATLAB
% handles structure with handles and user data (see GUI-
DATA)

a=imread('C:\efytest\efy.jpg');%%%%%%%%%
%% ENTER THE PICTURE LOCATION IN FILE HERE%%%%%%%%%
%%%%%%%%%
b=rgb2gray(a);
averaging=graythresh(b);
bw=im2bw(b,averaging);
[L,num]=bwlabel(bw,8);
detectedobjects=regionprops(L,'basic');
i=0;
for j=1:num;
if (detectedobjects(j).Area)>2500;
    i=i+1;
end
end
h=ones(5,5)/25;
convolution=imfilter(a,h);
imwrite(convolution,'C:\efytest\efy.jpg'); %%%%%%%%%% ENTER
THE PICTURE LOCATION WHERE THE EDITED PICTURE IS TO BE STORED
HERE%% %%%%%%%%%%
new=imread('C:\efytest\efy.jpg');%%%%%%%%%
%% ENTER THE PICTURE LOCATION OF THE EDITED FILE HERE%%%%%%%%%
%%%%%%%%%
new1=rgb2gray(new);
averaging1=graythresh(new1);
bw1=im2bw(new1,averaging1);
[L1,num1]=bwlabel(bw1,8);
detectedobjects1=regionprops(L1,'all');

i1=0;

for j1=1:num;
if (detectedobjects1(j1).Area)>2500;
    i1=i1+1;
end
end
ai=a(i,:,:),1;
imshow(ai);

clear

% --- Executes during object creation, after setting all
properties.
function text1_CreateFcn(hObject, eventdata, handles)
% hObject handle to text1 (see GCBO)
% eventdata reserved - to be defined in a future version of
MATLAB
% handles empty - handles not created until after all Cre-
ateFcns called

% --- Executes during object creation, after setting all
properties.
function text4_CreateFcn(hObject, eventdata, handles)
% hObject handle to text4 (see GCBO)
% eventdata reserved - to be defined in a future version of
MATLAB
% handles empty - handles not created until after all Cre-
ateFcns called

% --- Executes on button press in pushbutton5.
function pushbutton5_Callback(hObject, eventdata, handles)
% hObject handle to pushbutton5 (see GCBO)
% eventdata reserved - to be defined in a future version of
MATLAB
% handles structure with handles and user data (see GUIDATA)
cla

```

```

% --- Executes on button press in pushbutton3.
function pushbutton3_Callback(hObject, eventdata, handles)
% hObject handle to pushbutton3 (see GCBO)
% eventdata reserved - to be defined in a future version of
MATLAB
% handles structure with handles and user data (see GUIDATA)

a=imread('C:\efytest\efy.jpg');%%%%%%%%%
%% ENTER THE PICTURE LOCATION IN FILE HERE%%%%%%%%%
%%%%%%%%%
b=rgb2gray(a);
averaging=graythresh(b);
bw=im2bw(b,averaging);
[L,num]=bwlabel(bw,8);
detectedobjects=regionprops(L,'basic');
i=0;
for j=1:num;
if (detectedobjects(j).Area)>2500;
    i=i+1;
end
end
h=ones(5,5)/25;
convolution=imfilter(a,h);
imwrite(convolution,'C:\efytest\efy.jpg');%%%%%%%%% ENTER
THE PICTURE LOCATION WHERE THE EDITED PICTURE IS TO BE STORED
HERE%% %%%%%%%%%%
new=imread('C:\efytest\efy.jpg');%%%%%%%%%
%% ENTER THE PICTURE LOCATION OF THE EDITED FILE HERE%%%%%%%%%
%%%%%%%%%
new1=rgb2gray(new);
averaging1=graythresh(new1);
bw1=im2bw(new1,averaging1);
[L1,num1]=bwlabel(bw1,8);
detectedobjects1=regionprops(L1,'all');

i1=0;

for j1=1:num;
if (detectedobjects1(j1).Area)>2500;
    i1=i1+1;
end
end
ai=a(i,:,:),1;
imshow(ai);

clear

% --- Executes during object creation, after setting all
properties.
function text1_CreateFcn(hObject, eventdata, handles)
% hObject handle to text1 (see GCBO)
% eventdata reserved - to be defined in a future version of
MATLAB
% handles empty - handles not created until after all Cre-
ateFcns called

% --- Executes during object creation, after setting all
properties.
function text4_CreateFcn(hObject, eventdata, handles)
% hObject handle to text4 (see GCBO)
% eventdata reserved - to be defined in a future version of
MATLAB
% handles empty - handles not created until after all Cre-
ateFcns called

% --- Executes on button press in pushbutton5.
function pushbutton5_Callback(hObject, eventdata, handles)
% hObject handle to pushbutton5 (see GCBO)
% eventdata reserved - to be defined in a future version of
MATLAB
% handles structure with handles and user data (see GUIDATA)
cla

```