

Ethernet controller X540 and two copper interfaces. Existing infrastructures with common CAT6+ cables are sufficient to establish 10Gb interconnects.

XMC402 not only delivers high transfer rates but also efficient data throughput, as it unburdens the CPU by using intelligent mechanisms such as checksum offload, TCP segmentation offload and reduced interrupt operations.

By supporting Intel's virtualisation technology for connectivity including on-chip QoS and traffic management, flexible port partitioning as well as virtual machine device queues, XMC402 optimises bandwidth demands of even the most complex virtualisation solutions for current multi-core and multi-processor installations.

Kontron Technology India Pvt Ltd, Bengaluru

Fax: (080) 40831001

Phone: 40831004

Web: www.kontron.com

PIC32 GUI development board

Microchip Technology has introduced a PIC32 GUI development board with projected capacitive touch. This board makes it easy for designers to add the combination of multitouch projected-capacitive inter-



faces and high-quality 16-bit colour graphics to WVGA displays in any application.

Additionally, Microchip's 32-bit PIC32 microcontroller can directly drive LCDs, eliminating the cost and complexity of an external graphics controller. The on-board MTCH6301 projected-capacitive touch controller simplifies integration of popular multi-touch and gestures with greatly reduced design time and risk.

In combination with Microchip's

free graphics and multitouch software, this board is said to enable modern user interfaces for cost-sensitive designs in a broad range of markets such as consumer, industrial and medical.

Microchip Technology (India) Private Ltd,

Pune

Fax: (020) 25661513

Phone: 25661512

Web: www.microchipdirect.com

TEST & MEASUREMENT

USB 8-channel logic analyser

Lynx has introduced IDEofy LA-08 USB 8-channel logic analyser. This logic analyser is also a protocol analyser that can decode and analyse I²C, SPI, UART, 1-Wire, DCC and CAN bus. It can program each of the logic pins as a general-purpose input/output. Each



pin can be used to generate a 16-step PWM waveform.

Lynx, Chandigarh

Phone: (0172) 4628643

E-mail: sales@lynx-india.com

Web: www.lynx-india.com

MISCELLANEOUS

Fully digital 800W power supply

A new 800W bulk front-end power supply from Emerson Network Power meets the 80 PLUS Gold standard for efficiency. The DS800SL-3 power supply has a high efficiency of 92 per cent when operating at half-load from a 230V AC input, combined with a typical power factor in excess of 0.99.

With a high power density of 1.16W/cm³ in a slim-line rack-mounting package, DS800SL-3 enables system designers to minimise space



requirements in enterprise servers and similar space-constrained applications.

DS800SL-3 features a built-in FC serial bus interface and uses the industry-standard PMBus communications protocol. Developed primarily for systems employing distributed power architectures, the power supply has a wide input voltage range of 90 to 264V AC and is rated for 800W output power.

Arrow Electronics, Bengaluru

Phone: (080) 41353800

E-mail: ssessions@arrowuk.com

Web: www.emerson.com/EmbeddedPower

PowerLED flood light

Binay Opto Electronics has launched the 10050L PowerLED flood light. It replaces a 250W HPSV flood light or a 150W metal-halide flood light, with a total power consumption of 100 watts only. The light is compact,



measuring just 41x30.6x15 cm³. It offers a long life of more than 50,000 hours and cool light output. It is shock-resistant and vibration-proof, and can also withstand large variations in input voltage.

Binay Opto Electronics Pvt Ltd, Kolkata

Fax: (033) 22421493

Phone: 22429082, 22103807, 22102039

E-mail: info@binayLED.com

Web: www.binayLED.com