

single-cycle multiplier, nested vectored interrupt controller, built-in Flash memory from 4 kB to 16 kB, 2kB SRAM, configurable data flash, and high-speed high-performance communication interfaces such as SPI, I²C and UART. It also features an 8-channel, 10-bit SAR ADC, two-channel comparators, power-on reset and brown-out detect reset.

Spectra Innovations India, Bengaluru

Phone: (080) 42527888

E-mail: SpectraNuvoton@spectraind.com

RF digital-to-analogue converter

Maxim Integrated Products has launched a multi-Nyquist RF digital-to-analogue converter. The MAX5879 delivers a fully digital software-defined radio transmitter, enabling a common hardware platform for multicarrier, multiband and multistandard base stations.

Working with FPGA-based direct digital synthesis, the MAX5879 shifts the functions of the analogue quadrature modulator and agile local oscillator used in current architectures into the digital domain. This eliminates in-phase and quadrature errors and local-oscillator feedthrough, commonly associated with analogue up-conversion. The MAX5879 simplifies RF design and improves reliability for base-station transmitters.

Maxim India, Bengaluru

Fax: (080) 30285812

Phone: 30285800

High-power LED

Using a silicone lens and a uniquely designed ceramic substrate, the C350 LED from SemiLEDs features optimised brightness and efficacy, as well as excellent reliability. The LED's light output degradation is said to be less than 10 per cent under most stringent test conditions. It also features a special design-to-fit secondary optics for various emission angles. Users can easily achieve desired light uniformity with appropriate secondary optics.

SemiLEDs India, Gurgaon, Haryana

Phone: 9871155223

Email: sales@semileds.com

Web: www.semileds.com

µModule regulators

Linear Technology Corporation has introduced a 5µA quiescent-current DC-to-DC step-down µModule regulator with very low dropout voltage and a wide input and output voltage range of operation.

The LTM8029 includes an inductor, power switches, DC-to-DC controller and additional circuitry in a small BGA package. Efficiency of operation for 3.3V output at 600 mA from 5V, 12V and 24V input voltages is 84 per cent, 79 per cent and 75 per cent, respectively.

The LTM8029 has an adjustable switching frequency from 200 kHz to 2.2 MHz, which is useful for applications that must maintain switching noise within a certain range. In addition to stepping down positive to positive voltage, the LTM8029 can be used to regulate a negative output voltage.

Linear Technology, Bengaluru

Fax: (080) 40124612

Phone: 40124610

Web: www.linear.com

COMPUTING

Single-board computers

Kontron has launched the third generation of 3U OpenVPX single-board computers (SBCs) with latest interface technology based on the third-generation Intel Core i7 processors. These



SBCs come with native support for 10 Gigabit Ethernet and PCI Express 3.0 to meet the high bandwidth demands of network-centric military, aerospace and transportation applications.

The VX3042 and VX3044 are specifically designed to provide the ideal combination of leading-edge perfor-

mance, power efficiency and bandwidth to long-lifecycle applications.

By offering the highest speeds in PCI Express and Gigabit Ethernet on the VPX market, Kontron's 3U boards are said to offer the same bandwidth in half the size of existing solutions.

Kontron Technology India Pvt Ltd, Bengaluru

Fax: (080) 40831001

Phone: 40831004

Web: www.kontron.com

Industrial SSD

Apacer Technology has introduced the mSATA A1 modular



SSD that features a SATA 3.0 high-speed transmission interface. The new SSD complies with JEDEC MO-300 standard codes. It supports Intel's Rapid Start and Smart Response technologies, enabling users to enjoy an almost immediate start-up within seconds.

The SSD is only one-third the size of a credit card. With dimensions of 50.8x29.8 mm², it can streamline the space on the motherboard.

Apacer Technologies Pvt Ltd, Bengaluru

Fax: (080) 41700215

Phone: 41529061/62/63

E-mail: india_sales@apacer.com;

Web: www.apacer.com

TOOLS & EQUIPMENT

Winding machines

ACME Electronics has introduced CNC/programmable motor coil winding machines (Model AEH Series) for wire sizes from 7SWG to 50SWG with coil length up to 800 mm and winding length up to 500 mm.

The machines offer variable maximum speed of up to 750/1500 rpm

