

in the market a fan that cancels this noise. The company has developed an ultra-quiet ventilation system that uses the active noise control technology developed by Swedish specialist RotoSub. Active noise-cancellation involves pairing a sound wave with a wave of identical amplitude but inverted phase so that the noise and anti-noise effectively cancel out each other.

The system consists of a microphone, a metal band around the PC fan's frame and a signal processor. The microphone captures the sound being emitted by the fan and feeds that data to the signal processor, which analyses the noise and toggles magnets built into the tips of the fan's blades. As the magnets react to the band around the fan's frame, the blades vibrate to generate sufficient anti-noise to counteract much of the noise generated by the blades and motor.

World's smallest HD gesture recognition camera

SoftKinetic has come up with a pocket-sized camera called the DepthSense 325 (DS325) that sees both in 3D (depth) and high-definition 2D (colour). According to the company, developers can use the device to incorporate high-quality finger and hand tracking for PC video games, and introduce new video conferencing experiences. The DS325 can operate from as close as 10 cm and includes a high-resolution depth



SoftKinetic's DepthSense 325 camera

sensor with a wide field of view, combined with HD video and dual microphones.

The company has also developed the iisu 3.5 gesture-recognition middleware compatible with most 3D sensors available in the market. In addition to its robust full body tracking features, iisu 3.5 offers the capability to accurately track users' individual fingers at 60 frames per second, opening up a new world of close-range applications.


Supercomputer to use 'good old' tape storage

According to a ComputerWorld report, the National Center for Supercomputing Applications (NCSA) is building a storage infrastructure consisting of 380 petabytes of magnetic tape capacity and 25 petabytes of disk storage. This is being made to support the Blue Waters supercomputer. This supercomputer is being built to predict the behaviour of complex


BINAY Multichip LED Lamps

These multichip LED lamps are ideal for use in applications such as annunciator window fascia lighting and illuminated pushbutton switches

BA9S bayonet cap



E10 screw cap




Midget Groove




Midget Flange




5.5mm slide contact



6.8mm slide contact



Bi-pin type



Wedge Base




Also available in E5, E12, E14, and B14 base types



binay opto electronics private ltd.

44, Armenian Street, Kolkata 700 001, India
Tel: (033) 2210 3807, 2210 2039, 4006 9875
Fax: 91-33-22421493 Website: www.binayLED.com
Email: info@binayLED.com

Retrofit PowerLED Tube Light



The BINAY PowerLED Retrofit tubelight fits directly into a standard fluorescent tube luminaire or strip

- Wattage less than 50% of fluorescent system, with similar light output
- Operates from 100VAC to 260VAC (No flickering at lower voltages)
- Provides sharper visual clarity than fluorescent tube
- Life of 12 to 15 years, with a warranty of 5 years



binay opto electronics private ltd.

44, Armenian Street, Kolkata 700 001, India
Tel: (033) 2210 3807, 2210 2039, 2242 9082
Fax: 91-33-2242 1493, Website: www.binayLED.com
email: info@binayLED.com, binay@vsnl.com

INVENTING NEW TECHNIQUES OF PRODUCING LIGHT