

NEW PRODUCTS

RECENTLY INTRODUCED IN INDIA, FROM NEAR AND FAR

COMPONENTS

Femtocell transceiver

Maxim Integrated Products has introduced the MAX2550/51/52/53 femtocell transceivers for WCDMA (bands 1 to 6, and 8 to 10) and cdma2000 (band class 0, 1, and 10). These transceivers accelerate time-to-market. A MAX-PHY digital interface eliminates the additional cost and space typically incurred with external data converters.

The transceivers come in a 7x7mm² TQFN package and are rated over the -40°C to +85°C temperature range. These reduce the number of external components, facilitating more compact radio designs for modules and standalone femtocell applications.

Maxim India, Bengaluru

Fax: (080) 30285812

Phone: 30285800

RF transmitter

Semtech Corporation has announced a fully integrated, low-cost amplitude-shift keying/on-off keying radio transmitter designed to replace a surface-acoustic wave (SAW) based resonator transmitter in consumer remote control systems.



The SX1243 features a fractional-N phase-locked loop with 1.5KHz typical step, which minimises the bill-of-materials (BOM) cost. It covers frequency bands from 310 MHz to 450 MHz, 860


MHz to 870 MHz, as well as 902 MHz to 928 MHz, which makes it suited for worldwide operation.

Semtech India, Mumbai

Phone: (022) 23513759

Photocoupler

Renesas Electronics Corporation has introduced a photocoupler with a long external creepage distance of 14.5 mm. The photocoupler is suited for inverters in applications such as industrial equipment, and complies with safety standards covering the maximum com-



mercial power supply voltage of 690V or solar power generation systems employing high voltages up to 1000 V. The insulation voltage is 7500 Vrms.

The photocoupler employs a light-receiving IC, enabling it to achieve a low parasitic capacitance while keeping the circuit current below 3 mA and delivering short delay times of less than 150 ns.

Renesas Electronics, Bengaluru

Fax: (080) 67208777

Phone: 67208700

Web: <http://sg.renesas.com>

LED driver micro-modules

Texas Instruments has introduced two fully integrated LED driver micro-modules that eliminate the external components and complex layout placement challenges typical of LED driver designs. The 450mA DC-DC LED driver modules are said to be the industry's first to incorporate all the required power and passive circuitry into a single IC package to deliver up to 23W of power to the LED.

The 14W TPS92550 and 23W TPS92551 constant-current buck LED driver modules virtually eliminate the need for power supply design resources and simplify procurement, with just one module replacing four or more components. Together with TI's WEBENCH LED Architect, the lighting developer can quickly design a power management circuit with the minimum components needed to drive a string of 16 or more LEDs at up to 96 per cent power efficiency.

Texas Instruments (India) Pvt Ltd

Jasola District Centre, New Delhi

Phone: 1-800-425-7888 (toll-free)

Web: www.ti.com

UV LED chip

SemiLEDs has launched UV LED chips that are capable of emitting radiation at a wavelength of 390-420 nm with 40 per cent external quantum efficiencies at 350 mA (up to 500mW output power, typical 3.3V forward voltage). One of the chips in this series is the S50N-U, which is a high-power (3W/5W), high-brightness, 365nm UV LED in a sealed silicon package avail-



able in a ready-to-use format. It makes use of SemiLEDs' proprietary MvpLED technology. SemiLEDs UV LED products are available in wavelengths ranging from 365 nm to 420 nm, in chip sizes of 1.07x1.07 mm² and 0.3x0.3 mm².

SemiLEDs India, Gurgaon, Haryana

Phone: 9871155223

Email: sales@semileds.com

Web: www.semileds.com