

MOSFET power clip

Fairchild Semiconductor has introduced a 25V, $3.3 \times 3.3\text{mm}^2$ asymmetric dual n-channel MOSFET power clip. Developed to operate at higher switching frequencies, the FDP8011S consists of a $1.4\text{m}\Omega$ SyncFET and a $5.4\text{m}\Omega$ control, low-figure-of-merit n-channel MOSFET integrated in an all-clip package, which helps reduce the capacitor count and inductor size in synchronous buck applications.

The device allows simple placement and routing, enabling a more compact board layout and optimal thermal performance. It delivers over 25A output current and has a two times output current capacity improvement over other conventional $3 \times 3\text{mm}^2$ dual MOSFETs.

Fairchild Semiconductor (India) Pvt Ltd,
Bengaluru
Fax: (065) 64968762
Phone: 40407218

SiC JFETs

Infineon Technologies has introduced the CoolSiC 1200V SiC JFET family that is specially designed to increase the efficiency of solar inverters. These JFETs have much lower switching losses than IGBTs, which allows higher switching frequencies to be used without sacrificing the overall system efficiency. Alternatively, a higher-output power solution can be realised within the same inverter housing.

These JFETs are a complete solution consisting of JFET, p-channel MOSFET and dedicated driver. There is no reverse-recovery charge, thanks to unipolar MOSFET-like characteristics. The monolithically integrated body diode has a switching performance comparable to an external SiC Schottky barrier diode.

Infineon Technologies India Pvt Ltd,
Bengaluru
Phone: 800 4402951 (toll-free)



TOOLS & EQUIPMENT

Java development tools

STMicroelectronics, in partnership with Java tools specialist IS2T, has created ready-to-use Java development kits for its STM32 microcontrollers.



The STM3220G-JAVA starter kit combines an evaluation version of IS2T's MicroEJ software development kit and the STM32F2 series microcontroller evaluation board. MicroEJ provides extended features to create, simulate, test and deploy Java applications in embedded systems. Support for graphical user interface development includes a widget library, design tools including storyboarding, and tools for customising fonts. GeeseWare contributes to the ecosystem supporting Java for STM32 with its complete one-stop-shop hardware and software solution.

STMicroelectronics Pvt Ltd, Greater Noida
(UP)
Phone: (0120) 2352999
Web: www.st.com

Online IC design simulator

Fujitsu Semiconductor has introduced a Web-based design simulator for power management ICs. Easy



DesignSim offers comprehensive online design simulation and support for design engineers working with Fujitsu's line of power management ICs such as those in converters, switches, power supplies and charge control devices.

Engineers can use the simulator to validate or test their designs and power configurations right from the Fujitsu website. The tool calculates key power parameters such as input/output voltages, load currents, efficiency and switching frequency automatically, and then simulates the operation of the power supply online.

Fujitsu Semiconductor Asia Pte Ltd, Noida
Phone: (0120) 4541110
E-mail: fjalmarcom@sg.fujitsu.com
Web: www.sg.fujitsu.com

TEST & MEASUREMENT

Vibration meter

The Fluke 805 is a portable multi-function vibration screening tool. It measures overall vibration from 10 to 1000 Hz and provides a four-level severity assessment for overall vibration and bearing condition.

The meter detects peaks in the vibration signal readings of roller bearings from 4000 Hz to 20,000 Hz, and uses a proprietary algorithm to interpret severity to determine whether the bearing is going faulty. It has a unique sensor tip design that minimises measurement variations caused by device angle or contact pressure. This reduces error and improves the accuracy and repeatability of quick vibration screening.

TTL Technologies Pvt Ltd (a Fluke company),
Bengaluru
Fax: (080) 25251859
Phone: 25260646, 25251859 (Extn 22)
Web: www.tthindia.com

