

The devices feature real burst, which simulates the natural appearance of the burst phenomena or sweep to simulate the bouncing of an electrical contact. The IFM and DFM functions (increasing and decreasing frequency) are useful for investigating the resonance or saturation effects in the tested device.

The generator simulates quick transient noise interference. The single pulses show 5-nanosecond rise-time and a wide radio frequency spectrum up to 300 MHz.

Scientific Mes-Technik Pvt Ltd, Indore
E-mail: marketing@scientificindia.com
Web: www.scientificindia.com

Clamp meter

TTL Technologies has introduced Fluke's 771 clamp meter for programmable logic controller and control system analogue input/output that can measure 4-20mA signals without breaking the loop.

The clamp meter measures milliampere signals with 0.01mA resolution. The detachable clamp with extension cable allows measurements in tight locations. Its built-

in spotlight illuminates hard-to-see wires in dark enclosures.


TTL Technologies Pvt Ltd, Bengaluru
Web: www.ttlindia.com

WLAN test platform

National Instruments has introduced a test solution for next-generation 802.11ac WLAN chipsets and devices. The test solution provides flexibility in testing 802.11ac devices in addition to 802.11a/b/g/n devices. It works with signal bandwidths including 20, 40, 80 and 80+80 160 MHz for both transmitter and receiver for up to 4x4

multiple-input and multiple-output configurations.

The 802.11ac solution features modulation formats up to 256 QAM, optional MAC features such as LDPC,



STBC and AMPDU, and automated test system development using NI LabVIEW, C or Microsoft Visual Studio.

NI Systems (India) Pvt Ltd, Bengaluru
Phone: (080) 41190000
E-mail: ni.india@ni.com

COMPUTING

Industrial server

Kontron Technology has added KTQM67 to Kontron industrial silent server (KISS) family in 1U mini 48.3cm (19-inch) rack format. The server is



based on second-generation Intel Core i3/i5/i7 processors, and has one PCI Express x16 extension slot for graphics and framegrabber cards. It offers numerous peripherals and networking options via 8x USB 2 (6x rear, 2x front) and 3x GbE-LAN. For data storage, there is a shock-resistant internal 8.9cm (3.5-inch) slot, plus slots accessible from the front for a 8.9cm hard disk and a slim DVD drive.

Kontron Technology India Pvt Ltd, Bengaluru
Fax: (080) 40831001
Phone: 40831000
Web: www.kontron.com

FRAMS

Fujitsu Semiconductor has introduced ferroelectric RAMs (FRAMS) based on its 0.18µm technology. The MB85RC16V and MB85RC64V have an I²C interface and represent density

levels of 16 and 64 kbits, respectively.

The devices operate off 3V-5.5V, and feature an endurance of one trillion read/write cycles and data retention for ten years at 85°C. Maximum operating frequency is 400 kHz. The devices come in EEPROM-compatible 8-pin plastic small-outline packages with standard memory pin assignment.

Fujitsu Semiconductor Asia Pte Ltd,
Bengaluru
Fax: (080) 28416660
Phone: 28419990

Web: www.fujitsu.com

Graphics cards

MSI has released two graphics cards. The R7770-2PMD1GD5/OC and R7750-PMD1GD5/OC feature Radeon HD 7700 GPU based on AMD's



28nm process with support for PCI Express Gen3. Core voltage adjustment is supported by the MSI R7700 graphics card.

The graphics cards feature a customised dual-fan thermal design. Other features include integrated support for 3D video, high-quality DisplayPort 1.2 and HDMI 1.4a outputs, and AMD's Eyefinity multiple display output technologies.

Neoteric, New Delhi
Fax: (011) 40524279
Phone: 40524270/81, 40524283
E-mail: delhi@neoteric.co.in

LIGHTING

LED down light

GlacialLight has added a 15.2cm (6-inch) TRIAC-dimmable LED down light to its Capella Series. GL-DL06D has both low-voltage and high-voltage models supporting 90-132V and 180-264V, respectively.