

It is available in three models—GL-DL06D-WW, GL-DL06D-NW and GL-



DL06D-CW. These have colour-correlated temperature of 3000K, 4000K and 6000K and luminous flux of 560 lm, 560 lm and 730 lm, respectively.

The all-in-one bulb and fixture down light consumes 12 watts. Meant for indoor use only, it lasts a minimum of 30,000 hours.

Lotus Insulation Services, Pune
E-mail: sales@lotusins.in

Aviation obstruction LED light

Binay Opto has introduced the MIA-DX-40KCD-W LED aviation obstruction light. This flashing white light is designed to meet the International



Civil Aviation Organisation (ICAO) requirement for a medium-intensity Type-A aviation obstruction light. It utilises a light source consisting of multiple stacks of high-intensity power LEDs mounted on reflector modules, configured to provide wide-angle dispersion. It offers 40,000-candela flashing effective intensity at 20-60 flashes per minute.

A facility for changeover to the lower-intensity requirement of ICAO Type A during night is available. A GPS facility can be incorporated for synchronised flashing of all such aviation lights on a structure.

Binay Opto Electronics Pvt Ltd, Kolkata

Fax: (033) 22421493

Phone: 22429082, 22103807

E-mail: info@binayled.com, binay@vsnl.com

STORAGE

Capless USB drives

PNY Technologies, Inc. has introduced Micro Attaché series USB Flash drives.

The capless drives are 3cm long and 1.2cm wide and come with a turquoise-coloured silicone jelly cover that is waterproof and dust-resistant.



Weighing 1.4 gm, Micro Attaché USB flash drives come in 2GB, 4GB, 8GB, 16GB and 32GB storage capacities. These are compatible with Windows 2000, Windows XP, Windows Vista, Windows 7, Mac OS: 10.3 and above. The drives offer data transfer speed of up to 32 MB/second.

Balaji Solutions Limited, Kolkata
Phone: (033) 66331600/22317525

6Gbps solid-state drive

Transcend Information has launched the SSD720 SATA III 6Gbps solid-state drive (SSD). Combining the latest SATA III 6Gbps specification with a SandForce-driven controller, the SSD offers up to 550MB/s read



and write speeds.

The 7mm thick SSD720 features support for native command queuing. It uses the same SATA connector as used on a 6.35cm (2.5-inch) hard disk drive and is backwards compatible with SATA II/I (3Gbps/1.5Gbps) interface.

Built with NAND flash memory, it contains no moving part. For Windows 7 users, it supports the TRIM command to automatically remove deleted data permanently. For operating systems that do not support TRIM command, the SSD720 utilises a garbage collection algorithm for free space management.

Supertron, Kolkata

Phone: (033) 22131221-23

TOOLS & EQUIPMENT

Development platform

NGX Technologies has introduced BlueBoard-LPC111XX prototyping solution. It is a ready-to-run development



platform with code snippets to demonstrate applications for every feature supported on the board.

The 110x110mm² BlueBoard features two-layer PCB (FR-4 material). On-board linear regulators generate +3.3V/500mA and +5V/500mA from power supply USB connector. Other features include 10-pin, 20-pin CORTEX debug connector for serial wire debug, 12MHz crystal for microcontroller, 32kHz crystal for real-time clock, extension headers for all microcontroller pins and 64x128 graphical LCD with backlight control.

NGX Technologies Pvt Ltd, Bengaluru

Phone: (080) 40925507