



Introducing 40 V – 250 V MOSFETs in High Current Package

Offering Optimized Performance and Cost for a Given Application

Standard Gate Drive

Part Number	Package	Voltage	Current	$R_{DS(on)}$ Max. @10V	Q_g Typ @10V
IRFH5004TRPBF	PGFN 5x6mm	40 V	100 A	2.6 mΩ	73 nC
IRFH5104TRPBF	PGFN 5x6mm	40 V	100 A	3.5 mΩ	53 nC
IRFH5204TRPBF	PGFN 5x6mm	40 V	100 A	4.3 mΩ	42 nC
IRFH5006TRPBF	PGFN 5x6mm	60 V	100 A	4.1 mΩ	67 nC
IRFH5106TRPBF	PGFN 5x6mm	60 V	100 A	5.6 mΩ	50 nC
IRFH5206TRPBF	PGFN 5x6mm	60 V	89 A	6.7 mΩ	40 nC
IRFH5406TRPBF	PGFN 5x6mm	60 V	40 A	14.4 mΩ	21 nC
IRFH5007TRPBF	PGFN 5x6mm	75 V	100 A	5.9 mΩ	65 nC
IRFH5207TRPBF	PGFN 5x6mm	75 V	7 A	9.6 mΩ	40 nC
IRFH5010TRPBF	PGFN 5x6mm	100 V	100 A	9.0 mΩ	67 nC
IRFH5110TRPBF	PGFN 5x6mm	100 V	63 A	12.4 mΩ	48 nC
IRFH5210TRPBF	PGFN 5x6mm	100 V	55 A	14.9 mΩ	40 nC
IRFH5015TRPBF	PGFN 5x6mm	150 V	56 A	31 mΩ	33 nC
IRFH5215TRPBF	PGFN 5x6mm	150 V	27 A	58 mΩ	20 nC
IRFH5020TRPBF	PGFN 5x6mm	200 V	43 A	55 mΩ	36 nC
IRFH5220TRPBF	PGFN 5x6mm	200 V	20 A	100 mΩ	20 nC
IRFH5025TRPBF	PGFN 5x6mm	250 V	32 A	100 mΩ	37 nC

Features

- Low thermal resistance to PCB (down to <0.5°C/W)
- High Current Package – up to 100A continuous
- 100% RG tested
- Low profile (<0.9 mm)
- Industry-standard pinout
- Compatible with existing surface mount techniques
- RoHS compliant containing no lead, no bromide and no halogen
- MSL1, industrial qualification

The IR Advantage

- Increased power density
- Increased reliability
- Multi-vendor compatibility
- Easier manufacturing
- Environmentally friendlier

Logic Level Gate Drive

Part Number	Package	Voltage	Current	$R_{DS(on)}$ Max. @4.5V	Q_g Typ @4.5V
IRLH5034TRPBF	PGFN 5x6mm	40 V	100A	3.2 mΩ	43 nC
IRLH5036TRPBF	PGFN 5x6mm	60 V	100A	5.5 mΩ	44 nC
IRLH5030TRPBF	PGFN 5x6mm	100 V	100A	9.9 mΩ	44 nC

For more information, please visit us at www.irf.com or www.irf.com.cn

International
IR Rectifier
THE POWER MANAGEMENT LEADER