



new Intel Advanced Vector Extensions (AVX) floating-point instructions, with integrated graphics and memory controller and the mobile Intel QM77 PCH chipset.

Arrow Electronics, Bengaluru
Phone: (080) 41353800
E-mail: ssessions@arrowuk.com

TEST & MEASUREMENT

Analogue capacitor ESR meter

Lynx has introduced a measurement and analysis tool from Creatronica (Argentina) that lets you check the internal equivalent series resistance (ESR) of capacitors, which cannot be tested by a capacitance meter.



This is an analogue instrument that has multiple scales for different ranges of capacitor values. It can test ESR from 0.1 microfarad to 9999 microfarads using AC voltage. It also has a DC test range to find shorted capacitors and can test transformers also.

Lynx, Chandigarh
Phone: (0172) 4628643
E-mail: sales@lynx-india.com
Web: www.lynx-india.com

IR thermometer

Fluke Corporation has introduced the VT02 visual infrared (IR) thermometer—a troubleshooting camera with an infrared heat map. Until now, industrial electricians, HVAC and automotive technicians have had to choose between single-point infrared thermometers and high-resolution thermal imagers (infrared cameras). The VT02 thermometer fills the gap when a single-spot temperature reading isn't enough and a high-resolution thermal image is more than users need.



This single tool combines the visual insight of a thermal imager, visual images of a digital camera, and the point-and-shoot convenience of an IR thermometer.

TTL India Pvt Ltd (A Fluke Company),
Mumbai
Fax: (022) 29207689
Toll-free: 1 800 209 9110
E-mail: info.india@fluke.com
Web: www.fluke.com/india

Digital audio and video analyser

National Instruments (NI) has launched the PXIe-1491 digital audio and video analyser for HDMI, DVI and mobile devices. Designed for performance testing and high-throughput test of consumer devices such as set-top boxes, Blu-ray players, smartphones and tablets, the PXIe-1491 delivers automated,



high-performance measurements to eliminate subjective manual inspection.

The PXIe-1491 is shipped with NI Video Measurement Suite—a test suite for analysing a wide variety of video standards. NI also offers add-ons such as AudioMASTER software, designed for in-depth audio testing including frequency response and THD, and picture quality analysis software.

NI Systems (India) Private Limited, Bengaluru
Fax: (080) 41190010
Phone: 41190000
E-mail: ni.india@ni.com
Web: http://india.ni.com

Switchable step attenuators

Rohde & Schwarz has introduced the RSC family of switchable step attenuators, including a step attenuator up to 67 GHz and a model with 0.1dB step size offering a high accuracy and stability.



The RSC family consists of four models of the R&S RSC base unit and two external step attenuators. The base unit is available with or without internal step attenuator. The internal step attenuators come in three versions and can handle signals up to max. 18 GHz. The two external step attenuators cover frequencies up to max. 67 GHz. Every base unit can control up to four external step attenuators in parallel.

The RSC step attenuators allow users to attenuate signal power step by step either manually or by remote control. A typical field of application is the calibration of measuring instruments, especially receiver linearity testing.
Rohde & Schwarz India Pvt Ltd, Delhi Office
Fax: (011) 425354-33
Phone: 425354-00
E-mail: sales.rsindia@rohde-schwarz.com
Web: www.rohde-schwarz.co.in