



Benefits

- ▶ Top-class spectrum analyzer measurement speed
- ▶ Best-of-class dynamic range at medium-class price
- ▶ XGA-color LCD Display at 1024 x 768 resolution, 213 mm (8.4 in)
- ▶ Lightweight at ≤ 15 kg (33 lbs)
- ▶ Size: 426 mm x 177 mm x 390 mm (16.7 in x 6.9 in x 15.3 in)

MS2830A Signal Analyzer Highlights

Frequency Ranges	9 kHz to 3.6 GHz (040), 9 kHz to 6 GHz (041), 9 kHz to 13.5 GHz (043) 9 kHz to 26.5 GHz (044), 9 kHz to 43 GHz (045)
Dynamic Range	168 dB (MS2830A-040/041/043) 159 dB @ 25 GHz (MS2830A-044/045)
DANL	-153 dBm/Hz (MS2830A-040/041/043) -146 dBm/Hz (MS2830A-044/045)
Third-Order Intercept (TOI)	≥ +15 dBm (MS2830A-040/041/043) +13 dBm (MS2830A-044/045)
SSB Phase Noise	-133 dBc/Hz @ 100 kHz offset with Option 066 (MS2830A-040/041/043) -115 dBc/Hz @ 100 kHz offset (MS2830A-044/045)