

Mid-Performance Handheld Instruments



Benefits

- ▶ Easy to use handheld compact spectrum analyzer for fast reliable measurements
- ▶ Field-proven design, rugged, compact with daylight viewable display
- ▶ Intuitive menu-driven touchscreen user interface
- ▶ 3 hour battery operation time
- ▶ Lightweight at 3.45 kg (7.6 lbs)
- ▶ Size: 273 mm x 199 mm x 91 mm (10.7 in x 7.8 in x 3.6 in)

MS271xE Spectrum Analyzer Highlights

Frequency Ranges	9 kHz to 3 GHz (MS2711E) 9 kHz to 4 GHz (MS2712E) 9 kHz to 6 GHz (MS2713E)
Dynamic Range	> 85 dB (2.4 GHz), 2/3 (TOI-DANL) in 100 Hz RBW (MS2711E) > 102 dB (2.4 GHz), 2/3 (TOI-DANL) in 1 Hz RBW (MS2712E/13E)
Interference Analyzer	Spectrogram, Signal Strength, RSSI
DANL	-142 dBm in 100 Hz RBW (MS2711E) with preamp option 0008 -162 dBm in 1 Hz RBW (MS2712E/13E)
Phase Noise	-90 dBc/Hz max @ 10 kHz offset at 1 GHz (MS2711E) -100 dBc/Hz max @ 10 kHz offset at 1 GHz (MS2712E/13E)
Frequency Accuracy	< $\pm$ 50 ppb with GPS On