

Installation & Maintenance

The Solutions

Some in field measurement applications require a spectrum analyzer with benchtop performance, features and bandwidth. Anritsu's high-performance handheld spectrum analyzers meet this need. These instruments include:

The MS2721B Spectrum Master™

Use: Highly accurate analysis of wireless LAN and cellular signals, including 802.11a, 3G, ultra-wideband, WiMAX, and wireless medical patient monitoring systems.

Its wide dynamic range and low phase noise make NRSC measurements on analog and IBOC signals easy, with no need for an external carrier notch filter. As a result, the MS2721B is well suited for AM and FM broadcast proofing.

With the MS2721B, demodulated signals can be monitored using an internal speaker or by using a universal 2.5 mm 3-wire headset, such as used with many cellular telephones. The use of compact flash memory modules or USB flash drives up to 32 GB allow an unlimited number of traces and setups to be stored.

For more information go to MS2721B Spectrum Master product page.

The MS2722C/23C/24C/25C/26C Spectrum Master™

Use: Spectrum monitoring, hidden signal detection, RF and microwave signal measurements, microwave backhaul testing and cellular signal measurements. Includes burst detect to see pulsed emitters that have pulse widths of 200 μ s or greater.

The MS272xC Spectrum Master features over 30 analyzers in one, to meet virtually every measurement need. It offers the industry's best sweeps speed to 43 GHz, three sweep modes, resolution bandwidths from 1 Hz to 10 MHz, zero-span capabilities that include 10 MHz resolution bandwidth and video bandwidth, and an enhanced spectrum analyzer graphical user interface. Collected data can be post processed on the MS272xC using Anritsu Master Software Tools. The Remote Access Tool allows the user to see and control the instrument over a LAN connection.

In addition to spectrum analysis, the user can select optional capabilities and analyzers such as a high accuracy power meter, interference analyzer, channel scanner, or GPS receiver, and 3GPP, 3GPP2 or IEEE 802.16 signal analyzers. Secure data operation, 140 MHz zero-span IF output, 30 MHz bandwidth and geo-tag data collection capabilities are also available.

For more information go to MS2722C/23C/24C/25C/26C Spectrum Master product pages.



Scan this code with your smartphone to download our "RF Interference Hunting Techniques" Application Note or visit www.anritsu-offer.com/SpA-India