

Installation & Maintenance

Our field installation and maintenance spectrum analyzers feature a full range of measurements and signal analysis options for all of the global standards around the world. Measurements provide answers to your toughest network and spectrum challenges.

Measurements

- ▶ Field Strength (uses antenna calibration tables to measure dBm/m², dBmV/m and other units)
- ▶ Occupied Bandwidth (measures 99% to 1% power channel of a signal)
- ▶ Channel Power (measures the total power in a specified bandwidth)
- ▶ ACPR (adjacent channel power ratio)
- ▶ AM/FM/SSB Demodulation (wide/narrow FM, upper/lower SSB), (audio out only)
- ▶ C/I (carrier-to-interference ratio)

Optional Capabilities

Interference Analysis (Option 25)	MS2712/13E, MS2721B and MS272xC
Channel Scanners (Option 27)	MS2712/13E, MS2721B and MS272xC
Power Meter (Option 29)	MS2712/13E, MS2721B and MS272xC
Tracking Generator (Option 20)	MS2711E/12E/13E, MS2721B
High Accuracy Power Meters* (Option 19)	MS2721B and MS272xC
Zero Span IF Output (Option 89)	MS272xC
I/Q Waveform Capture** (Option 24)	MS272xC

*Requires external power sensor, **Requires Option 9

Signal Analysis Options

Wireless Signal Analysis (MS2712/13E, MS2721B and MS272xC)

FDD and TDD LTE (Options 541, 542, 543, 546, 551, 552, and 556)
W-CDMA/HSPA+ (Option 44 and 65)
GSM/EDGE (Option 40 and 41)
CDMA, EV-DO (Option 42, 43, 62, 63)
TD-SCDMA/HSPA+ (Option 38, 60, 61)
Fixed and Mobile WiMAX (Options 46, 47, 66, and 67)

Digital TV Signal Analysis (MS2712/13E and MS2721B)

DVB-T/H (Option 57, 64, and 78)
ISDB-T (Option 30 and 32)