

Rotary position sensor

Bourns has announced the availability of a new non-contact magnetic rotary position sensor. The AMS22 uses mag-



netic Hall effect technology, which enables high-performance operation even in extreme temperature and unclean conditions. It has an analogue single output of 0.1-4.9V, with an effective electrical output of 340 degrees, and is programmable up to 360 degrees. The analogue output features 12-bit resolution and comes with independent linearity of 0.5 or 0.3 per cent.

Bourns Inc.

E-mail: asiacus@bourns.com
Web: www.bourns.com

Power-over-Ethernet controller

Edom Technology has introduced Silicon Labs' single-port power-over-Ethernet (PoE) controller. The plug-and-play Si3462 is a complete single-port PoE and PoE+PSE (power sourcing equipment) solution. When deployed with the new classification optional mode, it eliminates the need for up to ten discrete components.

The controller provides a variety of pin-selectable operating modes that enable flexible use of the device in both PSE endpoint and mid-span applications.

Edom Technology, Bengaluru
Phone: (080) 26780722

E-mail: ravikumard@edom-tech.com
Web: www.edom.com.tw/en/index.jsp

Analogue front ends

Texas Instruments has introduced the ADS1298 family of fully integrated analogue



front ends for portable biopotential measurement applications. The five new ECG and EEG analogue front ends are claimed to be the first to offer 16-bit and 24-bit resolution with single or dual channels.

All devices in the family have low-noise programmable gain amplifiers, test signals, right-leg-drive amplifier, oscillator, voltage reference and lead-off detection function to simplify design, while significantly reducing board space requirements and cutting power consumption.

Texas Instruments

Phone: 1-800-425-7888 (toll-free)
Web: www.ti.com

Transceiver for LTE applications

Fujitsu Semiconductor has introduced the MB86L13A LTE (FDD and TDD) optimised transceiver for LTE-only applications. The MB86L13A covers the frequency spectrum from 700 to 2700 MHz. It provides multiband LTE support on a single IC.

The advanced application programming interface minimises factory calibration time and adds monitoring of customised key performance indicators. The availability of multiple transmit, receive and diversity ports offers significant flexibility to map ports and bands for roaming requirements.

Fujitsu Semiconductor Asia Pte Ltd, Noida
Phone: (0120) 4541110

E-mail: fsa.marcom@sg.fujitsu.com
Web: www.sg.fujitsu.com

Receive front-end modules

Infineon Technologies has introduced receive front-end modules for implementation of global navigation satellite system functionality in smartphones and other handheld devices.



The BGM104xN7 series contains two modules for specific platform applications. The BGM1043N7 is a standard solution meeting high-performance GPS/GLONASS specifications, with 14.8dB gain and 1.5dB noise figure. The BGM1044N7 is a high-gain (17dB) version with 1.5dB noise figure for systems with high losses in the receive chain.

Infineon Technologies, Bengaluru

Fax: (080) 25131212

Phone: 25131000

Toll-free: 000 800 4402951

Web: www.infineon.com

TEST & MEASUREMENT

LCR meter

GW Instek has introduced a handheld LCR meter. The LCR-916/915 has dual displays (20,000- and 2000-count) and provides basic measurement accuracy of 0.2 per cent. The test frequency extends as high as 100 kHz/10Hz.

The meter provides two-wire and five-wire measurement methods and comes with various standard or optional accessories for different component types. It also includes functions such as data hold, tolerance sorting, zero mode and min/max. The USB interface can be used to log data to a PC using the LCR900 software.

Goodwill Instruments

E-mail: india_marketing@goodwill.com.tw
Web: www.gwinstek.com

