

Thanks!

The circuit idea 'Home Appliances Control Using Telephone' published in March issue was excellent. I have assembled it as my mini project. Thanks to EFY!

M. Nagasuresh
Through e-mail

Author Guidelines

I have developed a small do-it-yourself project. How do I get it published in EFY magazine?

Shankar D.

Kuala Lumpur, Malaysia

EFY: Please visit the following link for the guidelines: <http://electronicsforu.com/electronicsforu/articles/WI-EDT.pdf>

Source Code Download

From where can I download the source codes of projects 'Time-controlled Switch Using PIC16F72', 'Car Bonnet Light Control Using Tilt Sensor' and 'Digital Clock with AM and PM Display' published in the April issue?

Narendra Gupta

Temple Computers, Jaipur

EFY: You can download the source codes from the following link: <http://www.efymag.com/previousissue.asp?month=April&year=2012&tot=1&id=12>

Vehicle Parking System

I am assembling the construction project 'RFID-Based Automatic Vehicle Parking System' published in the January issue. What is the rpm of the motor used in the project?

Aditya Varahagiri

Pune

The author Bikramjeet Waraich replies: The rpm (revolutions per minute) of the DC motor used in the prototype is 100. The opening and closing of the door will depend on the delays used in the code. You can use a 50-rpm motor.

Water-level Controller

I am quite excited about assembling the project 'Automatic Water Level

Controller for Sump/Submersible Pump' published in EFY Sept. 2011. I plan to install and integrate it with my submersible pump, but have following queries:

1. On page 104, in Fig. 5, where do I connect the other ends of terminal inputs 3, 4, 5, 6, 7, 8 on the PCB: RL1 or RL2?

2. Where do I connect terminals 1 and 2—12V primary, relay RL1 or RL2?

Rajesh Deogiri

Through e-mail

The author B. Shankar Rao replies: Terminal block connections to the PCB are as given below:

Terminal	Connection
1	Phase input 220V AC
2	Neutral input
3	Neutral output
4	Phase output RL1
5 and 6	N/O contacts DPDT relay N/O1 contact for contactor point of starter button
7 and 8	DPDT relay N/O2 contact for capacitor point of starter button
9	Sensor A
10	Sensor B
11	Sensor C
12	Sensor D

Use suitable thick, insulated wires for connecting all the 220V AC points and also select suitable relay contact ratings as per the horsepower (HP) of your motor. To be on the safer side, use a 30-ampere contact rating useful for motors up to 2 HP because the starting current of a motor is almost double the normal running current.

In a sump motor, terminals 5, 6, 7 and 8 are not used. So you can avoid relay RL2 completely. The N/O contact of relay RL1 and pole terminals can directly be connected in series with the motor supply to switch off and switch on the motor automatically.

An MCB of suitable rating (see Fig. 5 in the article) can be connected in series with 220V AC phase input as a protective device to trip when

any accidental short circuit occurs. Alternatively, it can be connected as a bypass switch between terminals 1 and 4. This bypass switch will allow the pump to be operated manually when the controller is not functioning due to some problem. To use the bypass switch, turn off S6 first.

Use stainless-steel screws or wires as sensors to avoid corrosion. Cover with Mseal, nylon glue (by using a glue gun) or sealing wax the portion of the sensor to which wires are fixed so that water does not come in direct contact with the copper wire. Leave at least 5 mm of the tip of the sensor exposed so that it can come in contact with water and sense the water level in the tank. Good luck!

Moving Message Display

The 'Moving Message Display on

LCD' construction project published in Dec. 2011 issue of EFY uses a 6-pin berg strip male connector. I have not been able to find this

connector both in the market and online. Please help.

Nikhil
Makkar
Through
e-mail

EFY: A male berg strip is available in 40-pin package as shown in Fig. 1 here.

You can break it and make two rows with 3-pin connector at each row (refer Fig. 2).

Alternatively, you can get a 6-pin header box (refer Fig. 3) from the market.



Fig. 1: 40-pin male berg strip



Fig. 2: 6-pin connector



Fig. 3: 6-pin header box