


SUSPENSE SUSPENSE
SUSPENSE SUSPENSE
SUSPENSE SUSPENSE
SUSPENSE SUSPENSE
SUSPENSE SUSPENSE
SUSPENSE SUSPENSE



Are You In Suspense?

Are you wondering what happened to your order or payment, even after a fortnight? But did you mention your name and address clearly while sending payment, and what the payment was for?

We get several payments every month without adequate instructions or even identity of the person sending the payment. As a result we are unable to take appropriate action on these, till we get a complaint - if at all.

At EFY, we want you to be our satisfied customer. So please do let us know in case your payment or instructions are not even acknowledged within a fortnight. We are not that lazy!

Email: support@efyindia.com
Ph: 011-26810601 / 02 / 03 extn: 242




Fig. 4: Dual-IP stack architecture




Fig. 5: Tunneling using 6-to-4

IPv6 to coexist in the same devices and networks

2. Tunneling techniques that connect IPv6 domains via IPv4 clouds

3. Translation techniques that provide an interconnection between IPv4 and IPv6 domains to allow IPv6-only devices to communicate with IPv4-only devices

Dual IP stack. The basic IPv4-to-IPv6 migration technology uses dual IP stack protocol architecture, which connects IPv4/IPv6 nodes to IPv4-only nodes or IPv6-only nodes. This implementation incorporates IPv4 and IPv6 protocol stacks either independently or in a hybrid form. The application can use either protocol.

Dual-stack implementation has its own transport layer, which includes transmission control protocol (TCP) and user datagram protocol (UDP), and framing layer, which performs link layer encapsulation and decapsulation. Present systems share common transport and framing layers and are enabled by default.

When used in IPv4 communications, hybrid stacks use an IPv6 application-programming interface and represent IPv4 addresses in a special address format—the IPv4-mapped IPv6 address. This address type has its first 80 bits set to '0' and the next 16 bits set to '1,' while last 32 bits are filled with the IPv4 address.

Tunneling. Tunneling is a technique in which an isolated IPv6 host can communicate via IPv4 infrastructure. This is achieved by encapsulating IPv6 packets within IPv4, which is used as a link layer for IPv6. IP protocol number 41 indicates encapsulation of IPv6 datagrams within IPv4

packets.

Translation and proxy for IPv6-only hosts. In order to provide backward-compatibility for IPv6-only hosts to existing IPv4-only resources, translation and proxy mechanisms may be used. Network address translator (NAT) like technique (NAT64) for translation at the lower layers in routers and gateways may be considered. Dual-stack application-layer proxy server, a Web proxy, can also be used for address translation.

Benefits of IPv6 over IPv4

Larger IP address space. An enhanced address space, in the absence of NAT, provides less complex network hardware and software. Configuring a network becomes much simpler. Finally, the large availability of IP addresses removes any obstacle that existed previously in the full deployment of wireless and mobile devices.

Simplified and modular header structure. IPv6 has a simpler packet header structure than IPv4, designed