

ent types of IC package shapes.

The devices include VP-290, VP-390 in the low-cost range, VP-590



in the mid range and VP-990 in the high-end range series. Wellon also has production gang programmers in its profile.

Lynx, Chandigarh

Phone: 4628643

E-mail: sales@lynx-india.com

Web: www.lynx-india.com

TEST & MEASUREMENT

Stationary power quality analyser

Elspec has announced that the innovative design of the G4400 black-box device series is a technological breakthrough providing the perfect PQ analysis solution. Its enhanced capabilities are adaptable to address the individual needs and requirements for almost any business and/or application.

The G4K provides accurate detection and isolation of power quality monitoring for effective preventive maintenance. The G4000 black-box power quality analyser calculates RMS, harmonics and all desired values from waveforms in post-processing that includes calculation of over 10,000 parameters.

ELSPEC Engineering (India) Pvt Ltd, Mumbai
Phone: (022) 65346467
E-mail: info@elspec.in
Web: www.elspec.in



Multiport optical power meters

Agilent Technologies Inc. has introduced extensive optical power-meter portfolio in the market. The two-channel N7747A and four-channel N7748A bring the industry-leading sensitivity of the 81634B sensor module to the compact multichannel N77 platform, with updated memory size and data-transfer speed.



The Agilent N7747A and N7748A optical power meters enable engineers to make parallel multiport measurements and monitor weak signals and small signal changes with high precision in, for example, communications or sensing applications. The meters can detect power levels down to -110 dBm and log data at intervals down to 25µ with up to 1 million points per channel. An equally large data buffer supports simultaneous measurement and data transfer.

Agilent Technologies India, New Delhi

Fax: (0124) 1800-11-3035

Phone: 2292009

Web: www.agilent.co.in

Earth testers clamp

Megger has announced its new Earth testers clamp with elliptical apertures that can accommodate cables up to 39mm diameter and flat earth tapes up



to 50mm wide. The DET14C and DET24C earth resistance clamp testers are said to be quick and easy to use, even with large conductors and in applications where access to conductors is restricted.

In addition,

these instruments are the first of their type to have a CATIV 600V safety rating in line with EN61010, with 8 kV of transient isolation, and operator safety is further enhanced by a hazardous current warning that is operative on all test ranges.

Megger (India) Pvt Limited, Mumbai

Fax: (022) 26740465

Phone: 26740468

Web: www.megger.com/in/

Power quality analyser

Hioki E.E. Corporation has launched the PW3198, a new power quality analyser. The instrument, which complies with the IEC 61000-4-30 Ed. 2 Class A international standard on power quality measurement, provides superior quality power measurement capability.



Compliance with the international standard on power quality measurement, which stipulates the most stringent requirements in the field, points to the PW3198's unparalleled functionality and reliability. To comply with the standard, the instrument delivers basic voltage measurement precision of 0.1 per cent, an improvement of 200 per cent over the previous model.

Hioki India Private Limited, Indore

Fax (0731) 4020083

Phone: 4469195

E-mail: info@hioki.in

Measurement software

Anritsu Corporation has recently launched its new MX882012C-021 LTE-Advanced FDD DL CA measurement software for its popular MT8820C radio communication analyser supporting the world's first all-in-one measurement tester, a solution for LTE-Advanced call-processing tests.