

The MT8820C integrates the signal generator, signal analysis and base station simulation functions required for R&D and manufacturing of mobile appliances in a compact all-in-one platform. It is the next generation mobile communications system offering mobile subscribers faster data speeds than LTE.

Anritsu India Private Limited, Bengaluru
Phone: (080) 405 81300
Web: www.anritsu.com/en-US/home.aspx

PicoScope upgrade

The PicoScope 6 oscilloscope software can now decode I2S data, thanks to the latest software update from Pico Technology. The I2S (Inter-IC Sound) standard is a common serial data format used in audio equipment such as CD players and DACs.



All PicoScope users can download the new beta release free of charge. As well as I2S, the software can decode I2C, RS-232/UART, SPI, CAN, LIN and FlexRay serial data.

PicoScope's serial decoding is easy to use, with decoded data displayed on the same axes as the waveform so you can compare analogue and digital domains.

Analytical Electronics Services Pvt Ltd,
Gandhinagar
Fax: (079) 23287266
Phone: 29289167, 23287267
E-mail: sales@analyticalelectronics.in
Web: www.analyticalelectronics.in

MISCELLANEOUS

PowerLED retrofit tubelight

Binay Opto Electronics has launched the Binay Model PENTA 3300 23W PowerLED retrofit tubelight. It is a

direct retrofit (in-place replacement) for the standard fluorescent tubelight, and can be directly replaced in the existing luminaire with minimal modification.

The product is covered under patent application No. 843/Kol/2010 dt. 02.08.2010, and is indigenously



designed and manufactured in India.

The product is covered under a warranty of 5 years (for most models), with an estimated life of 12-15 years.

Binay Opto Electronics Pvt Ltd, Kolkata
Fax: (033) 22421493
Phone: 22429082, 22103807, 22102039
E-mail: info@binayLED.com
Web: www.binayLED.com

Ultra-cool field metrology well

Fluke Calibration has introduced the 9190A ultra-cool field metrology well, a small, lightweight and accurate dry-block calibrator with best-in-class stability.

The 9190A is ideal for pharmaceutical, biomedical and food processing applications that demand strict quality control and regulatory process compliance, including on-location validation and calibration of RTDs, thermocouples, thermometers and other temperature sensors.

TTL Technologies Pvt Ltd, Bengaluru
Fax: (080) 25291285
Phone: 25260646, 25251859
E-mail: calibration.india@fluke.com
Web: www.fluke.com/india

Magnetic sensors

The new M5-22XM tubular threaded brass sensors series available with M6,

M8, M10 and M12 thread are claimed to be the perfect rugged and sturdy magnetic sensor solution for harsh environments or robust assembly conditions.

Nickel-plated brass housings and nuts resist high mounting forces and



adverse usage conditions. They allow an adjustable switching point; mains voltage variants are also possible.

PIC GmbH is a supplier for Reed Sensor Technology.

Millennium Semiconductors, Mumbai
Fax: (022) 27421486
Phone: 27484800
E-mail: mkt9@millenniumsemi.com
Web: www.millenniumsemi.com

AC-DC converter

Nuteck Products has launched a switch mode power supply (SMPS) or AC-DC converter, which is designed to take high-voltage spikes and surges.

Basic advantages of SMPS over linear power supply are its high efficiency, compact size, better line and



load regulation, and light weight. This could be used in industrial automation products, control panels, medical electronics, CCTVs, etc.

It can withstand 440VAC phase to phase supply and it is designed to meet EN61000-6-3, EN61000-4-4/5/6 standards.

Nuteck Product, Pune
Phone: 26811161/2
E-mail: pramod@nuteckproducts.com
Web: www.nuteckproducts.com