

```
cd /etc
```

```
nano hostname
```

'nano' is the Linux text editor. Change the host name to your chosen name for the server, like labserver in




Fig. 9: Hosts file




Fig. 10: Editing servername.conf




Fig. 11: MySQL password



Fig. 12: phpMyAdmin login page

our case (see Fig. 8).

Save the file by pressing 'ctrl + o' and exit 'nano' by pressing 'ctrl + x.'

Now edit '/etc/hosts' as follows:

```
nano hosts
```

Add the lines:

```
127.0.0.1localhost
xxx.xxx.x.xxx localhost
xxx.xxx.x.xxx labserver
```

In this, localhost is the standard TCP/IP host name and 127.0.0.1 is the standard IP address for local reference to the current physical machine. Replace 'xxx.xxx.x.xxx' with IP address of Raspberry Pi noted earlier, and labserver with your server name. Save the hosts file and exit the nano editor (see Fig. 9).

Create file 'servername' in '/etc/apache2/conf.d' directory using command:

```
sudo nano servername.conf
```

Type your server name in 'ServerName' directive as shown in Fig. 10:

```
ServerName labserver
```

Save the servername.conf file and exit the nano editor.

These changes will remove the error concerning

apache2 not finding the server name. Now stop/start apache2 service with the command already mentioned above.

Now you can test apache2 from your remote workstation by typing 'http://xxx.xxx.x.xxx' in the address bar of the browser. Replace 'xxx.xxx.x.xxx' with Raspberry Pi's IP address.

If you wish, instead of the IP address, you can type the name of your server on the address bar. For this, you need to add the following line in your windows host file, which is generally in 'c:\windows\system32\drivers\etc\':

```
xxx.xxx.x.xxx labserver
```

(Put Raspberry Pi's IP address and the name of the server.)

Install PHP programming environment

Execute the following command for installing the PHP5 environment:

```
apt-get install php5 libapache2-mod-php5 php5-intl php5-mcrypt php5-curl php5-sqlite
```

Install MYSQL database management system

Run the following command to install the MSQL database management system:

```
apt-get install mysql-server mysql-client php5-mysql
```

You will be asked to enter the password for the top-level MSQL user (see Fig. 11).

The username is root but you can enter the password of your choice. Also note that this is the managing user for MSQL and is nowhere related to root user of the Raspberry operating system. Stop and start apache2 server again after this installation.

Test MYSQL installation by logging into MYSQL. Use the root user and execute the following command:

```
mysql -u root -p
```

Enter the password when asked.

Install APC support package for PHP

APC is an alternative support system