

meet energy standards and they are compatible with efficient driver systems. They have holders and clamps ready for mounting and are perfect match with reflectors and lenses. They are ROHS compliant and have features like 33V forward voltage, die direct bonding to copper and very high thermal conductivity. The new COB series is suitable for street lighting, retrofit bulbs, spotlights, downlights.

SemiLEDs India, Gurgaon

E-mail: sales@semileds.com

Diode bridge controller

Linear Technology Corporation has introduced LT4320, an ideal diode bridge controller for 9V to 72V systems that replaces each of the four diodes in a full-wave bridge rectifier with a low-loss N-channel MOSFET to significantly reduce the power dissipation and increase available voltage.



The power supply size is reduced as the enhanced power efficiency eliminates bulky heat sinks. Low voltage applications benefit from the extra margin afforded by saving the two diode drops inherent in diode bridges. Compared to the traditional alternative, the MOSFET bridge enables a rectifier design that is highly space- and power-efficient. The controller operates from DC to 600 Hz.

Linear Technology India, Bengaluru

Ph: (080) 40124610

E-mail: snayak@linear.com, dawn@linear.com

Web: www.linear.com

DeepCover Secure Authenticator

Maxim Integrated Products, Inc. has launched DS28E35 DeepCover Secure

Authenticator, a highly secure cryptographic solution for a host controller to authenticate peripherals. The DS28E35 integrates a FIPS 186-based, elliptic curve digital signature algorithm (ECDSA) engine to implement asymmetric (public-key) cryptography to operate a challenge-and-response authentication protocol between a host controller and attached peripherals, sensors, or modules.

Operating over a single pin on the 1-Wire interface, the DS28E35 reduces interconnect complexity, simplifies designs, and reduces cost. It provides crypto-strong authentication security for many applications, including medical sensors, industrial programmable logic controller (PLC) modules, and consumer devices.

Maxim Integrated Products, Inc., Bengaluru

Ph: (080) 30982813, 09886277984

E-mail: mridula.benjamin@2020msl.com

POWER SUPPLY

1500W AC-DC power supply

Emerson Network Power has launched a new 1500W AC-DC power supply that unlike many other units in the market does not require any derating at low line and provides the full power across the input range of 90 to 264 Vac.



The LCM1500Q-T4 is the latest model in Emerson's popular LCM series of AC-DC power supplies, which is known for providing high efficiency and reliability at a competitive cost. This model is rated for 24V single output, which can be trimmed to ± 10 per cent.

Emerson Network Power India, Mumbai

Ph: (022) 67208000, 67208001

E-mail: anshul.kumar@emerson.com

Web: www.emersonnetworkpower.com

DC-DC converters

Recom Asia has introduced the following DC-DC converters—RH, RV, RP, RGZ, RKZ, RxxPxx and RxxP2xx, which are especially designed for IGBT driver circuits. Their asymmetric outputs of +15 V and -9 V make them ideal for power IGBT drivers, so now just one converter is needed where previously two were required.

The modules are available with input voltages of 5V DC, 12V DC and 24V DC and offer up to 6.4kV DC/second isolation. The converters operate reliably at temperatures between -40°C and +90°C without derating and with an efficiency of up to 85 per cent.

Recom Asia Pte Ltd, Singapore

Ph: 18003000388 (Toll free)

E-mail: enquiry@recomasia.com

Web: www.recomasia.com

TEST & MEASUREMENT

Sampling oscilloscopes

Pico Technology has launched PicoScope 9300 series sampling oscilloscopes that can perform pre-compliance tests, fault-finding, design, debug and margin testing on serial communication signals such as 10Gb Ethernet, SONET/SDH STM64 and FEC1071, 10x Fibre Channel, and InfiniBand and PCI Express.

These two-channel oscilloscopes can replace traditional, full-sized bench-top instruments without compromising on usability, analysis features or accuracy. The compact, full-featured PC-based sequential sampling oscilloscopes offer a unique combination of portability, price and performance. Their small size allows one to position them right next to the device under test, minimising cable losses and removing the need for expensive active probes or pull-out sampling modules.

There is even a built-in signal generator with 4ns minimum bit interval in PRBS mode and 8ns minimum period in pulse mode. The devices have LAN and USB interfaces, and advanced display features such as colour and density profiling, mul-