

and operated directly from an R&S ZNB network analyser.

The matrix combines excellent RF properties with high switching speed and long-life semiconductor switches, offering users an easy-to-use multiport vector network analyser with outstanding measurement characteristics.

*Rohde & Schwarz India Pvt Ltd, New Delhi
Phone: (011) 42535400*

E-mail: sales.rsindia@rohde-schwarz.com

Web: www.rohde-schwarz.com

Vibration meter

MetraVi introduces digital pen-type vibration meter model PVB-820. It is a small handheld comprehensive instrument that can measure acceleration, velocity and displacement. Just one switch for all measurements. The instrument has auto power off facility to save battery life.



Acceleration is measured from 0.01 to 199.9m/s, velocity from 0.01 to 199.9m/s and displacement from 0.001 to 1.999mm (peak-peak value). The frequency response is 10Hz to 1kHz for acceleration and velocity while for displacement it is 10Hz to 500Hz.

MetraVi Instruments Pvt Ltd, Kolkata

Fax: (033) 22154821

Phone: 22151376, 22159759

E-mail: info@metravivib.com

New precision pressure calibration products

Fluke Corporation is broadening its suite of precision pressure calibration products with the addition of 14 new 700G series pressure gauges and two new models of pressure calibrators:

Fluke 719Pro and 721 dual-range pressure calibrator.

Instrument, process and plant maintenance technicians now have a complete line of rugged, trusted pressure-calibration devices, allowing them to customise the gauge to meet their specific pressure calibration requirements.

TTL Technologies Pvt Ltd, Bengaluru

Phone: (080) 25260646, 25251859

E-mail: sudeep.zachariah@tfluke.com

Web: www.fluke.com/india

TOOLS & EQUIPMENT

Multi-purpose automated fabrication machine

Fuji launched the SmartFAB, a modular multi-purpose automated fabrication machine that automates manual assembly work to save labour and achieve high productivity as well as high quality.

SmartFAB supports various forms of parts such as radial parts, axial parts, trays, sticks and bowl feeders, and has the ability to handle part sizes from 1608 mm (0603-inch) to 190 × 190 mm, with heights that go up to 110 mm and weighs up to 200 gm.

Fuji Electric India Pvt Ltd

Phone: +91-22-40104870/71, 42524850

E-mail: info@fein.fujielectric.com

Web: www.fujielectric.co.in

New software platform builder

Altium Ltd has launched a software platform, delivering ultra-rapid prototyping and development for ARM Cortex-M-based microcontrollers, at an unparalleled attractive cost level.

The software platform, which Altium will be showcasing at the ARM TechCon Conference, includes a comprehensive range of middleware functionalities, such as an RTOS, CAN, USB, TCP/IP, I2C, HTTP(S), file systems, graphical user interface and touch panel control.

Altium India, Bengaluru

Phone: 9591591919, 9036604755

E-mail: sreekanth.tanmanu@altium.com

Web: http://altium.com/en/solutions/

ecad-meets-mcad

LEDs & LED LIGHTING

70-CDM Power LED Downlighter

The Binay model 70-CDM PowerLED Downlighter is designed as a practical light-equivalent replacement for replacing a 70W CDMT (ceramic discharge metal-halide lamp) fitting, which is widely used in retail as well as in industry.

With a system power consumption of around 30-35W, this product has less than half the power consumption of the CDMT lamp (which has a total system power of around 80-85W with the ballast). The high colour rendering index of 85 (typical) provides good rendition of colours (particularly important in retail applications).

Binay Opto Electronics Pvt Ltd, Kolkata

Fax: (033) 22421493

Phone: 22102039

E-mail: info@binayLED.com

Web: www.binayLED.com

Floodlight solutions

GlacialLight introduced models with standard AC input, DC input and PIR sensors in its floodlight series. These cater to indoor and outdoor architectural lighting needs in commercial, industrial and residential environments. Special functions include solar-powered lighting and security-enhancing illumination.

These LED

floodlights consume far less energy than mercury floodlights with an

average lifetime that is at least ten times beyond that of traditional halogen lamps. They are long-lasting and have low maintenance costs, with features like high-strength glass, anti-corrosion surface treatment, aluminium die-cast housing, corrosion-resistant stainless-steel braces and skid-proof screws. Lights are available in two colour temperature options—warm white (3000K) and cool white (5700K).

Argos International Marketing Pvt Ltd, Mumbai

Phone: (022) 30642000

E-mail: info@argos-infll.com

