

Electronics Rocks!

The Kits'n'Spares workshop at Electronics Rocks was cool! And for me it was like a tutorial. A big thanks for the T-shirt! I am planning to conduct a presentation on Mango Pi robot in my college too.

EFY Group has unmatched transparency. I have recommended monthly subscription of EFY to at least 50 friends in my college.

Himanshu Sharma

Through e-mail

EFY: Thanks for your kind words! We are happy to learn that you found the workshop useful. And super happy to note that you are recommending *Electronics For You* amongst fellow students.

Seven-Colour LED Lighting

The 'Seven-Colour LED Lighting' circuit published in November issue is nice. But there are 2-lead LEDs (Chinese make) already available in the market. The 2-lead LED produces multicolours while flashing and also produces a fading effect. This LED does not need any additional circuitry for all these functions.

So why would anyone attempt to make a circuit like yours when a complete circuit is available in the form of an LED?

Amit

Kolkata

The author Riju Thazhathuveetil replies:

I thank the reader for showing interest in my article. The published circuit is not only an LED flashing circuit but also produces a running lights effect. The circuit uses six RGB LEDs to generate a running lights effect one by one in seven colours: blue, green, red, cyan, yellow, magenta and white.

The readily-available 2-lead LED only produces different colours but we cannot control the colour display as desired. The sequence of colour display can be controlled with my circuit. That is the speciality of this circuit using 3-lead RGB LED.

USB Data Acquisition

I read the 'Make Your Own USB Data Acquisition' construction project pub-

From electronicsforu.com: Circuits

□ The 'Ethernet Interface for Automation Systems' construction project published in May issue is a very good project to be used in a distributed control system communication.

V. Jayaganesan

□ In the 'AC-Powered LED Lamps Without Rectifiers' circuit published in May issue, can you please tell me from where the input is to be given and how?

Saahil

The author Petre Tzv. Petrov replies: The input is on the connector CON1 side. It is for 220-230V, 50-60Hz AC mains voltage. T1 and T2 are for expansion of the lamp.

□ Can we modify 'Simple Stereo Power Amplifier With 7905' circuit published in June issue to drive two 4-ohm, 30W tweeters and one 16-ohm, 15W speaker for bass?

Nilav

The author Petre Tzv. Petrov replies: You can drive any load under the condition that the ICs are not overloaded. But this given circuit was just a demonstration on unusual application of 79XX. You can use the same method with 78XX, LM317, LM337 and similar regulators. If you use 2A, 3A, 5A and 10A linear regulator, you will have more output power. Also, under some restriction, you can connect the regulators in parallel and you will have more power. But in all cases that is not a competitor of classical audio amplifier.

Also, please note that it is a Class A amplifier. It consumes a lot of power!

'Spot An Error' Award Winners

□ In e-Style First Look section, under heading 'LG G2 has excellent display quality', it is mentioned that secondary 2.1 MP front camera comes with an LED flash whereas only rear 13 MP camera comes with an LED flash.

Siddharth Kaul

□ In the circuit idea 'A Simple Low-cost Audio Mixer' published in November issue, R25 is mentioned as 100 kilo-ohm instead of 1 kilo-ohm in the parts list.

Praveen S. Javali

lished in October issue but where can I get LabVIEW software? Please let me know about the .pdf or other learning materials available for LabVIEW software.

Maulik Patel

Through e-mail

The author Arun Dayal Udai replies:

Thanks for reading my article! The 'National Instruments' LabVIEW: The System Design Software' in EFY Plus September issue is a good one to follow up.

There are lots of technical resources available on NI website at <http://www.ni.com/labview/technical-resources/which> will help you learn

from scratch. NI has a great forum that will surely help you if you have an Internet connection. Once you register on the NI website, LabVIEW can be downloaded for free from <http://www.ni.com/trylabview/>

Environment Monitoring System

I want to know whether you have used MQ7 carbon monoxide sensor in 'Environment Monitoring System Using Arduino' construction project published in August issue. I want to know the code for conversion of analogue value from sensor to ppm for calibration purpose.

Amit

Through e-mail

The author Ronie Adhiraaj Ghosh replies: You need to refer to MQ7 datasheet and find the equivalent graph of ppm vs voltage output (using an external resistor) and compute an approximate equation related to the points in graph. But please note that this interfacing is not as accurate as industrial sensors and it only gives a rough approximation of gas quantity present. The procedure of getting equation is to note the points from the graph given in the datasheet and calculate a best-fit linear equation and load the program into the MCU.