

HVLED815PF

One-chip LED driving solution with high power factor



High power factor off-line LED driver with constant output current and primary-sensing regulation (PSR).

KEY FEATURES

- High power factor (>0.94)
- 3 % accuracy on constant LED output current with primary control
- Optocoupler not needed
- 800 V avalanche-rugged internal power MOSFET
- Internal high-voltage start-up
- Quasi-resonant operation mode
- Safe against open or shorted LED string
- Automatic self supply
- Input voltage feed-forward for mains independent constant-current regulation
- SO16N package

KEY BENEFITS

- Highly efficient solution thanks to the high power factor
- Reduced external part count to allow very small form factors and simplified design
- Robustness and compactness is guaranteed thanks to the internal power MOSFET and HV start up
- Accurate primary-current control avoids the use of secondary sensing, reducing costs and complexity

TARGETED APPLICATIONS

- AC-DC LED driver applications
- LED retrofit lamps



Evaluation Board	Main application power range	Application Configuration	Part number/Package
EVALHVLED815W15	Up to 15 W in 230 V mains	Flyback	HVLED815PF/ SO16N
EVLHVLED815W10F	Up to 10 W in 110V-230V mains	Flyback	HVLED815PF/ SO16N
EVLHVLED815W10A	Up to 10 W in 110V-230V mains	Buck Boost	HVLED815PF/ SO16N
EVLHVLED815W8CV	Up to 8 W in 230 V mains	Flyback – constant voltage	HVLED815PF/ SO16N

For any further information you can visit www.st.com/hvled or contact distributors

www.st.com

Distributors: Asia/Lucky: Abhijit, +91 88265 06060 • Avnet: Uday, +91 99808 99000 • Future: Tushar, +91 99000 93873
• WT: T. Meganathan, +91 98866 57305 Arrow: Manish, +91 98866 61615 • Tomen: Priti, +91 98197 94974 • EDOM: Raghunatha. G, +91 81304 26926
• Yosun: Anurag, +91 99106 45646 • Teck: Sumit, +91 98997 35127