

TABLE IV
Vibration Meters from Different Manufacturers

Specifications		Fluke Fluke 805	Metrix™ Model: VB 8202A	MCM Instruments VIBRATION TESTER AVD - 80	Extech Instruments Extech 407860
Range	Low frequency	10Hz-1000Hz	10Hz	10Hz	10Hz
	High frequency	4000Hz-20,000Hz	1000Hz	1000Hz	1000Hz
Vibration limit		50g peak (100g peak-peak)	0.1-4000g		200mm/s
Sample rate	Low frequency	20,000Hz	10Hz		
	High frequency	80,000Hz	1000Hz		
Signal-to-noise ratio		80dB			
Sensor	Sensitivity	100mV/g $\pm 10\%$	Piezoelectric		
	Measurement range	0.01g-50g	0.1-400.0 m/s		
	Resolution	0.01g		0.1mm/s	0.5m/s ² , 0.5mm/s, and 0.05mm
Safety	Accuracy	At 100Hz $\pm 5\%$ of measured value	5% ± 2 digits	$\pm (2\% + 0.1\text{mm/s})$	$\pm 5\% \pm 2$ digits
IP rating		IP54			
Dimensions		241 $\times$ 71 $\times$ 58mm	140 $\times$ 70 $\times$ 30mm		180 $\times$ 72 $\times$ 32mm
Weight (gm)		1160	150	200	395

features of some vibration meters from different manufacturers.

These are all the basic equipment that a field engineer would need de-

pending on the project at hand. You can also add a multimeter to the list, which is also a useful tool in many cases. Refer buyers' guide on handheld

digital multimeters published in February 2013 issue for details. ●

The author is a technical editor at EFY



support@ efyindia.com

**Do you have a query,
suggestion or a complaint?**

**You can e-mail it to
support@efyindia.com
and we will take care
of the rest.**



electronics
FOR YOU
www.electronicsonline.com

ELECTRONICS
BAZAAR
www.eb.effyindia.com

OpenSource
FOR YOU
www.linuxforu.com

Facts
FOR YOU
www.fymag.com

EFY
UNIVERSITY TOURS
www.efyindia.com