

Wi-Fi Embedded Webcam

The 'Wi-Fi Embedded Webcam' construction published in September 2013 issue is a very good project. We are doing this project now. Our PC has in-built wireless module but we are not able to find the Wi-Fi module in the Windows.

Ashtosh Mishra
Through e-mail

The author Muthiah Kathiresan replies:
Some PCs are equipped with both Ethernet and wireless modules. Just connect the Ethernet port of the PC to Ethernet port of any wireless modem and configure the wireless modem as SSID=kathir and security=none. Camera board can be placed at some distance near the main circuit. Once they are connected successfully via a wireless modem, LCD will display the IP address depending on the local network setup included in 'dhcpcd' program.

USB data acquisition

I am a regular reader of EFY and I made some successful projects from EFY. I

'Spot An Error' Award Winners

❑ In the 'USA Style Twin Horn' circuit published in January 2014 issue on page 106, the value of VR1 (in Fig. 1) is 100-kilo-ohm. But it is wrongly printed as 10-kilo-ohm in the parts list.

Praveen S. Javali

❑ In the 'Rotation Counter' circuit published in January issue on page 100, switch S1 is wrongly mentioned at test point TP4 in the table. It should read as 'Normally low and goes high when switch S2 is pressed.' The low-to-high reset pulse will be provided to the IC by switch S2.

Madhuran Mishra

❑ In 'Wireless FM Microphone' circuit published in the January issue, 12V is wrongly mentioned at test point TP1 in the table. TP1 should be 9V.

Adil Khan

❑ In the 'Arduino-Based Gauss Meter' construction project of January issue in Fig. 1 on page 97, pins 2 and 3 of IC2 (WSH315) are wrong. Pin 2 should be GND (Ground) and pin 3 should be Vout.

Siddharth Kaul

From electronicsforu.com: Circuits

Which Arduino kit is used in 'Environment Monitoring System Using Arduino' construction project published in August 2013 issue? Can I make this project without using the Arduino kit?

Gajanan Tejab Borkar

The author Ronie Adhiraj Ghosh: You can use Arduino UNO Diecimila or any other kit with minor modification in the code. Moreover, you can also make it using the ADC without Arduino. You can use traditional AVR, PIC or MSP430 microcontrollers with internal ADCs and write equivalent programs for them. I used Arduino for faster development. Note, if logic works, it will work on any microcontroller.

From Facebook: EFY's Electronics Design Community

I want the circuit diagram of 'Line Follower Robot.'

Sunny Gupta

EFY: You may refer to 'Automated Line Following Robot' circuit available on www.electronicsforu.com website under 'MCU Projects' section.

❑ I have been reading EFY since 1995 and have done more than 500 projects. Now I am working as a control and instrumentation engineer at Panipat Thermal Power Station. Thanks EFY!

Deepak Mittal

EFY: Thanks for the feedback!

need help in the project 'Make Your Own USB Data Acquisition System' published in October 2013 issue to design and fabricate the PCB.

G. Karthikeyan
Through e-mail

The author Prof. Arun Dayal Udai replies: I used NI Circuit Design Suite version 10.0. You may refer to my article 'Creating Professional Circuit Designs Using NI Circuit Design Suite' published in EFY November 2010 issue. To fabricate the PCB, you need Gerber files to be generated from NI software. You can contact any good PCB manufacturer and send the Gerber files to them. I got it done from www.pcbpower.com, which is an Ahmedabad-based firm.

Voice Recorder and Playback

I got 'Voice Recording and Playback' circuit from one of the EFY issues. But

the APR9600 IC used in that circuit is not available. Do you have any other circuit for sound recording?

Sanjiv Atre
Pune

EFY: We published 'Voice Recorder and Playback' circuit in October 2013 issue. The circuit is based on APR9301-V2 IC. You may contact our associates Kits'n'Spares at info@kitsnspares.com to get the issue or complete kit.

Android-Powered Access Control

I have one query in 'Android-Powered Access Control Via Bluetooth' construction project published in July 2013 issue. The default password in the program is set to 555. With hardware remaining the same how can I change the password?

Mosin Shaikh
Through e-mail

EFY: Download the accesscontrol.ino file of this project from source.efymag.com or copy it from EFY DVD of July 2013 issue. Open the source code (accesscontrol.ino) using Arduino IDE, change the password in .ino sketch, compile it and burn the code into the microcontroller.

ERRATA

In 'Simple Tester for Dual Operational Amplifier' circuit published in December 2013 issue, please read TLE061 as TL062 or TLE062.

Petre Tzv. Petrov
The author